

## CHEMISOL QUICK START SPRAY

CHEMISOL Quick Start Spray is a high-quality product, suitable for starting internal combustion engines.

- ✓ **Fast action**
- ✓ **Ether-based**
- ✓ **Misty spray pattern**

### APPLICATIONS

Recommended for diesel and gasoline engines.

### INDICATIONS

The spray must be at room temperature. The best temperature of use should be from 5°C to 30°C.

Before use, shake the spray can for 2 minutes and spray a sample. The distance to the surface to be treated should be approximately 25 to 30 cm.

### INSTRUCTIONS

Before use, shake the spray can.

Insert the CHEMISOL Quick Start Spray into the air inlet of the air filter for several seconds.

Start the engine.

### TECHNICAL SPECIFICATIONS

|                           |                                   |
|---------------------------|-----------------------------------|
| Color                     | Transparent                       |
| Base                      | Diethyl ether and mineral oil     |
| EU-VOC solvent percentage | ≈ 99,5% w/w                       |
| Odor                      | Characteristic                    |
| Relative density at 20°C  | 0,711 g/ml                        |
| Yield                     | 1,70 g/seconds                    |
| Steam pressure at 20°C    | 3 to 4 bar                        |
| Flashpoint                | - 40°C                            |
| Explosion Limit           | Lowest 1.7Vol.% / Highest 36Vol.% |

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.



| SAP       | ml  | Shelf Life |  | EAN           |
|-----------|-----|------------|---|---------------|
| CHC020318 | 400 | 10 years   | 12  | 5604630050289 |

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.