





CHEMIMOUNT MOUNTING GLUE WATER BASED

CHEMIMOUNT Mounting Glue Water Based is a water based acrylic adhesive, which adheres to all common building surfaces.

- Easy to apply √
- Paintable
- Solvent-free
- Forms permanently water repellent layer after curing \checkmark
- Odourless \checkmark
- \checkmark Wide range of applications
- \checkmark Extremely high bond strength.

APPLICATIONS

Bonding plasterboard to wood, PVC, thresholds, ceramic tiles. Installing wooden construction elements, decorative wooden trimmings, plasterboards, mouldings, skirting boards and panelling. Suitable for the adhesion of polystyrene tiles and polystyrene foams.

INSTRUCTIONS

Application temperature is between +5°C to +40°C. Make sure the surface to be applied is dry and clean, free of dust and grease Cut the cartridge tip and place it in the gun. And then, cut the cannula tip and insert into the cartridge. Apply the liquid nail





TECHNICAL SPECIFICATIONS

Chemical Basis	Acrylic Dispersion	
Skin Formation Time	30 - 60 minutes	
Complete curing time	24 Hours	
Ultimate elongation	Greater Than 100 %	
Elastic modulus at 100%	≥ 0,2 mPa	
Max. tensile strength	≥ 0,3 mPa	
Tensile strength	≥ 0,1 N/cm ²	
Density	1,63 ± 1,69 g/cm ³	
рН	7,5 - 9	
Application temperature	+5°C - +40°C	
Storage temperature	+5°C - +35°C	

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life	\diamond	EAN
CH05010001	310	36 months	24	5604630079143

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.