

## CHEMISOL CARBURETTOR CLEANER SPRAY

CHEMISOL Carburettor Cleaner Spray is a high-quality product, suitable for the interior and exterior of carburetors and valves, without the need for disassembly.



- ✓ **Direct spraying**
- ✓ **High dissolving properties**
- ✓ **Leaves no residue**
- ✓ **Non-corrosive**

### APPLICATIONS

Recommended for interior and exterior cleaning of carburetors and valves.

### INDICATIONS

The surface must be clean, dry and degreased. Sand the surface.

The spray must be at room temperature. The best temperature of use should be from 5°C to 30°C.

Before use, shake the spray can for 2 minutes and spray a sample. The distance to the surface to be treated should be approximately 25 to 30 cm.

### INSTRUCTIONS

Before use, shake the spray can.

- 1° Stop the engine and let it cool down. Remove the air filter.
- 2° Spray the outside surface of the carburettor until the dirt has disappeared.
- 3° Spray the visible parts from the inside of the carburettor.
- 4° Start the engine at a very limited speed.
- 5° Spray the CHEMISOL Carburettor Cleaner Spray several times on the air inlet and increase the engine speed.
- 6° Switch off the engine and install the air filter.



## TECHNICAL SPECIFICATIONS

Color	Transparent
Base	Hydrocarbons
EU-VOC solvent percentage	100% w/w
Odor	Characteristic
Relative density at 20°C	0,84g/ml
Yield	3,0 g/seconds
Touch	After 10 to 20 minutes
Steam pressure at 20°C	3 to 4 bar
Flashpoint of the active substance	< 21°C

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC020201	400	10 years	12	5604630050081

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.