



<section-header><section-header><section-header>

CHEMISOL COPPER GREASE SPRAY

CHEMISOL Copper Grease Spray is a high copper content to prevent wear and sticking of screwed connections exposed to very high temperatures.

- ✓ High thermal stability
- ✓ Resistant to chemicals and weather influences
- Prevents wear and corrosion
- ✓ Excellent adhesion
- ✓ Simplifies future removal
- ✓ Direct spraying

APPLICATIONS

Recommended for brake parts, exhaust system parts, threaded joints exposed to high temperatures, battery poles and spark plug threads. For repairing copper and other non-ferrous metal parts or pipes. Repair of pipe leaks by sealing wet surfaces or with small water leaks. The product eases handling of parts exposed to temperatures from -30°C to +1100°C.

INDICATIONS

The spray must be at room temperature. The best temperature of use should be from 5°C to 30°C.



INSTRUCTIONS

Before use, shake the spray can.

Apply the **CHEMISOL** Copper Grease Spray. The specific lubricating property is achieved after solvent evaporation (approximately 1 minute).





TECHNICAL SPECIFICATIONS

Color	Copper		
Base	Extreme pressure grease and small copper particles		
EU-VOC solvent percentage	≈ 69% w/w		
Solid content	≈ 31% w/w		
Odor	Characteristic		
Appearance	Pasty		
Yield	1,26 g/seconds		
Relative density at 20°C	0,767 g/ml		
Steam pressure at 20°C	3 to 4 bar		
Temperature resistance	-40°C to +1100°C		

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life	\bigotimes	EAN
CHC040103	400	10 years	6	5604630059510

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.