

CHEMISOL CUT AND DRILL LUBRICANT SPRAY

CHEMISOL Cut and Drill Lubricant Spray is a high-quality lubricant, suitable for preventing metals overheating during cutting and drilling works.

- ✓ **Protects and lubricates tools**
- ✓ **Reduces tool wear**
- ✓ **Reduces temperatures during cutting or drilling**
- ✓ **No silicone**
- ✓ **Non-corrosive**

APPLICATIONS

Recommended for cutting, sawing, turning, milling and drilling operations. Can be used on the majority of metals.

INDICATIONS

The spray must be at room temperature.

The best temperature of use should be from 5°C to 30°C.

INSTRUCTIONS

Before use, shake the spray can.

Before starting, generously spray the tool and material with water. The tool and material should remain moist during the activities.

TECHNICAL SPECIFICATIONS

Color	Light Brown Transparent
Base	Mineral oil
EU-VOC solvent percentage	≈ 50% w/w
Odor	Characteristic
Yield	1,77 g/seconds
Relative density at 20°C	0,85 g/ml
Steam pressure at 20°C	3 to 4 bar

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.



SAP	ml	Shelf Life		EAN
CHC040102	500	10 years	12	5604630050364

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.