

## CHEMISOL GREASE SPRAY

**CHEMISOL** Grease Spray is a high-quality product with PTFE, suitable for lubricate metal or plastic mechanical parts.

Recommended for use in the food industry according to NSF H1 registration.



- ✓ **NSF registered product\***
- ✓ **Extraordinary mechanical and thermal stability**
- ✓ **Good adhesion**
- ✓ **Prevents wear and sticking**
- ✓ **High viscosity**
- ✓ **Resistant to weather influences**
- ✓ **Resistant to weak acids and base**
- ✓ **Excellent in corrosion prevention**
- ✓ **Water-repellent**
- ✓ **Direct spraying**

### APPLICATIONS

Recommended for metal and plastic connections, springs, worm wheel, bearings, door hinges, conveyor belts. Extremely suitable for lubricating parts susceptible to intense pressure due to their high viscosity.

Spray especially suitable for machines and equipment in the food industry.



### INDICATIONS

The spray must be at room temperature. The best temperature of use should be from 5°C to 30°C.

Before use, shake the spray can for 2 minutes and spray a sample. The distance to the surface to be treated should be approximately 25 to 30 cm.

### INSTRUCTIONS

Before use, shake the spray can.

Apply **CHEMISOL** Grease Spray in a thin layer.

\* National Sanitation Foundation registration NSF-H1, number 139848

## TECHNICAL SPECIFICATIONS

Color	Beige
Base	Mineral oil with extreme pressure mass
Contains	PTFE (Polytetrafluoroethylene)
EU-VOC solvent percentage	≈ 71% w/w
Odor	Characteristic
Appearance	Greasy
Relative density at 20°C	0,76 g/ml
Yield	1,5 g/seconds
Steam pressure at 20°C	3 to 4 bar
Temperature resistance	-30°C to +160°C
pH	Neutral

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC010107	500	10 years	12	5604630050050

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.