

CHEMISOL MACHINE CLEANER SPRAY

CHEMISOL Machine Cleaner Spray is a high-quality product suitable for removing dirt on both treated and untreated metal surfaces.

Recommended for use in the food industry according to NSF H1 registration.



- ✓ **NSF registered product ***
- ✓ **High dissolving properties**
- ✓ **Removes a-polar preservatives (oil, grease, wax, undercoating and tar)**
- ✓ **Leaves no residue**
- ✓ **Non-corrosive**

APPLICATIONS

Suitable for machinery, walls, tools, floors and work tables. For removal of apolar preservatives such as oil, grease, wax, undercoat and tar on both treated and untreated metal surfaces.

Specially indicated spray for machines and equipment in the food industry.

INDICATIONS

The spray must be at room temperature. The best temperature of use should be from 5°C to 30°C.

Before use, shake the spray can for 2 minutes and spray a sample. The distance to the surface to be treated should be approximately 25 to 30 cm.

INSTRUCTIONS

Before use, shake the spray can.

Spray the parts to be treated evenly with the **CHEMISOL** Machine Cleaner Spray and let it work for a few minutes. Clean with water.



TECHNICAL SPECIFICATIONS

Color	Transparent
Base	Aliphatic and emulsifying hydrocarbons
EU-VOC solvent percentage	100% w/w
Odor	Characteristic
Relative density at 20°C	0,76 g/ml
Yield	2,2 g/sec
Steam pressure at 20°C	3 to 4 bar
Refractory index at 20°C	1,421
Flashpoint of the active substance	54°C

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC010108	500	10 years	12	5604630050067

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.