

CHEMISOL MACHINE OIL SPRAY

CHEMISOL Machine Oil Spray is a high-quality product with excellent penetration properties, suitable for equipment preservation.

Recommended for use in the food industry according to NSF H1 registration.



- ✓ **NSF registered product***
- ✓ **Extraordinary mechanical and thermal stability**
- ✓ **Excellent penetrating properties**
- ✓ **Moisture repellent**
- ✓ **Corrosion preventive**
- ✓ **Solvent-free**
- ✓ **Direct spraying**

APPLICATIONS

Spray suitable for chains, screwed connections, gear wheels, filters, bearings, valves, pistons, fasteners (screws, dowels and nuts). Extremely suitable for removing rust from oxidized parts.

Spray specially indicated for machines and equipment in the food industry

INDICATIONS

The spray must be at room temperature. The best temperature of use should be from 5°C to 30°C.

Before use, shake the spray can for 2 minutes and spray a sample. The distance to the surface to be treated should be approximately 25 to 30 cm.

INSTRUCTIONS

Before use, shake the spray can.

Apply the CHEMISOL Machine Oil Spray and let it work.

* National Sanitation Foundation registration NSF-H1, number 139848



TECHNICAL SPECIFICATIONS

Color	Transparent
Base	Mineral oil
EU-VOC solvent percentage	≈ 30% w/w
Odor	Characteristic
Relative density at 20°C	0,73 g/ml
Yield	2,5 g/seconds
Steam pressure at 20°C	3 to 4 bar
Temperature resistance	-20°C to +150°C
pH	Neutral

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC010104	500	10 years	12	5604630050029

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.