



CHEMISOL MULTI FOAM SPRAY

CHEMISOL Multi Foam Spray is a high-quality universal cleaning foam, suitable for light contamination.

- ✓ **Removes smoke, paint and grease deposits**
- ✓ **Easy to use**
- ✓ **Very efficient**
- ✓ **High dissolution**
- ✓ **Mild odour**
- ✓ **Water-based**

APPLICATIONS

Recommended for counters, paintings, walls, tiles, toilets, surfboards, kitchen cabinets, furniture, cars, doors, solariums and garden furniture.

INDICATIONS

The spray should be at room temperature.

Best processing temperature is between 5°C and 30°C.

INSTRUCTIONS

Before use, shake the spray can.

Apply CHEMISOL Multi Foam Spray and let it work. Remove the dirt with a dry and clean cloth.

TECHNICAL SPECIFICATIONS

Color	Transparent
Base	Surfactant solution
EU-VOC solvent percentage	≈ 25% w/w
Odor	Characteristic
Appearance	Foam
Relative density at 20°C	0,96 g/ml
Steam pressure at 20°C	5,5 to 6,5 bar
Coverage	≈ 4 m ²
pH	9,5 – 10,5

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC030102	400	10 years	12	5604630050319

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.