

## CHEMISOL ULTRA OIL SPRAY

**CHEMISOL** Ultra Oil Spray is a high-quality universal lubricant with PTFE to lubricate and protect metal and plastic parts. Recommended for use in the food industry according to NSF H1 registration.



- ✓ **NSF registered product \***
- ✓ **Excellent penetrating properties**
- ✓ **Moisture and water repellent**
- ✓ **Corrosion preventive**
- ✓ **Direct spraying**

### APPLICATIONS

Spray suitable for chains, tools, skates, skateboards, machinery, fastening (screws, bolts and nuts) and conveyor belt.

Spray specifically indicated for machines and equipment in the food industry.

### INDICATIONS

The spray must be at room temperature. The best temperature of use should be from 5°C to 30°C.

Before use, shake the spray can for 2 minutes and spray a sample. The distance to the surface to be treated should be approximately 25 to 30 cm.

### INSTRUCTIONS

Before use, shake the spray can.

Apply the **CHEMISOL** Ultra Oil Spray in the desired quantity.

As a result of a unique formula, it forms a protective coating.

\* *National Sanitation Foundation registration NSF-H1, number 139848*



## TECHNICAL SPECIFICATIONS

|                           |                           |
|---------------------------|---------------------------|
| Color                     | Transparent               |
| Base                      | Synthetic oil with Teflon |
| EU-VOC solvent percentage | ≈ 72% w/w                 |
| Odor                      | Characteristic            |
| Relative density at 20°C  | 0,71 g/ml                 |
| Yield                     | 2,1 g/seconds             |
| Steam pressure at 20°C    | 3 to 4 bar                |
| Temperature resistance    | -40°C to +250°C           |

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

| SAP       | ml  | Shelf Life |  | EAN           |
|-----------|-----|------------|---|---------------|
| CHC010105 | 500 | 10 years   | 12  | 5604630050036 |

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.