



## CHEMISOL V BELT SPRAY

CHEMISOL V Belt Spray is a high-quality product, suitable for the protection of belts to remedy and prevent sliding.

- ✓ **Easy to use**
- ✓ **Remedies and prevents slipping and creaking**
- ✓ **Excellent adhesion**
- ✓ **Lasting protection**
- ✓ **Dilatant**
- ✓ **Resistant to weather influences**
- ✓ **Conditions V-Belts**
- ✓ **Delays the wear of V-Belts**
- ✓ **Direct spraying**

### APPLICATIONS

Recommended for vehicles, machinery, conveyors, agricultural machinery, drills, presses, concrete mixers, lathes, lawnmowers, generators, compressors, forklifts, pumps and milling machines.

### INDICATIONS

The spray must be at room temperature. The best temperature of use should be from 5°C to 30°C.

Before use, shake the spray can for 2 minutes and spray a sample. The distance to the surface to be treated should be approximately 25 to 30 cm.

### INSTRUCTIONS

Before use, shake the spray can.

Switch off the engine.

Apply CHEMISOL V Belt Spray evenly in a thin layer on the V-belt notches and let it work. After evaporation of the solvent, start the motor.

## TECHNICAL SPECIFICATIONS

Color	Transparent
Base	Polyalphaolefin
EU-VOC solvent percentage	≈ 93% w/w
Odor	Characteristic
Relative density at 20°C	0,89 g/ml
Yield	1,15 g/seconds
Steam pressure at 20°C	3 to 4 bar

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC020319	400	10 years	12	5604630050296

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.