



CHEMISOL VASELINE SPRAY

CHEMISOL Vaseline Spray is a viscous, protective, high-quality lubricant. Recommended for use in the food industry according to NSF H1 registration.

- ✓ NSF registered product*
- ✓ Water-repellent
- ✓ Excellent adhesion
- ✓ Prevents wear and sticking
- ✓ Resistant to weather influences
- ✓ Resistant to salt water, weak acids and base
- ✓ Excellent corrosion prevention
- ✓ Misty spraying

APPLICATIONS

Recommended for battery poles, fasteners (screws, bolts, nuts and nails), electrical connections, conveyor belts and rails.

INDICATIONS

The spray must be at room temperature. The best temperature of use should be from 5°C to 30°C.

Before use, shake the spray can for 2 minutes and spray a sample. The distance to the surface to be treated should be approximately 25 to 30 cm.

INSTRUCTIONS

Before use, shake the spray can.

Apply CHEMISOL Vaseline Spray in a thin layer.

* National Sanitation Foundation registration NSF-H1, number 139848

TECHNICAL SPECIFICATIONS

Color	Beige
Base	Vaseline
EU-VOC solvent percentage	≈ 85% w/w
Odor	Characteristic
Relative density at 20°C	0,66 g/ml
Yield	1,1 g/seconds
Steam pressure at 20°C	3 to 4 bar
Drop point	42°C – 60°C
Temperature resistance	-30°C to +160°C
pH	Neutral

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC010101	400	10 years	12	5604630049993

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.