

## CHEMISOL HAMMER FINISH PAINT

CHEMISOL Hammer Finish Paint is a high-quality paint with hammered effect.



- ✓ **Fast-drying**
- ✓ **Good coverage**
- ✓ **Scratch-free and shockproof**
- ✓ **Resistant to gasoline, chemicals, diluted cleaners and weather influences**

### APPLICATIONS

Recommended for wood, metal, aluminium, glass, stone and different types of plastic.

### INDICATIONS

The surface should be clean, dry and degreased.

Remove old and loose varnish, rust and sand the surface.

Apply a layer of primer suitable for the surface. After drying, sand the base coat (grain 600).

The spray must be at room temperature. The best temperature of use is between 15°C and 25°C. Before use, shake the spray can for 2 minutes and spray a sample. The distance to the surface to be treated should be approximately 25 to 30 cm.

### INSTRUCTIONS

Apply a thin first layer. After a few minutes apply the topcoat. Before applying the next layer, shake the spray can again.



After use, clean the valve (turn the can upside down and press the nozzle for approximately 5 seconds until only gas comes out).

The drying time depends on the room temperature, air humidity and thickness of the product applied.

## TECHNICAL SPECIFICATIONS

Base	Alkyd resin
EU-VOC solvent percentage	≈ 82% w/w
Solid content	≈ 18% w/w
Coverage	1,25 to 1,75 m <sup>2</sup>
Drying	After 5 to 10 minutes
Touch	After 10 to 20 minutes
Hardening	After 24 hours
Temperature resistance	Up to 110°C

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP		ml	Shelf life		EAN
CHC060301	Blue	400	10 years	6	5604630051439
CHC060302	Green	400	10 years	6	5604630051446
CHC060303	Silver	400	10 years	6	5604630051453

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.