

CHEMISOL INDUSTRIAL CHAIN GREASE SPRAY

CHEMISOL Industrial Chain Grease Spray is a high-quality lubricant for use on all types of chains and wire ropes, which are susceptible to heavy loads.



- ✓ **Good adhesion**
- ✓ **Dilatant**
- ✓ **Prevents wear and sticking**
- ✓ **Exceptional mechanical and thermal stability**
- ✓ **Resistant to weather influences**
- ✓ **Resistant to weak acids and base**
- ✓ **Water-repellent**

APPLICATIONS

Suitable for chains, chain drives under heavy loads and belts. Can be used on hinges, boat engine parts and machines working at high speed.

INDICATIONS

The spray must be at room temperature.

The best temperature of use is between 5°C and 30°C.

INSTRUCTIONS

Before use, shake the spray can. The surface must be clean, dry and degreased.

Apply the chain spray in a thin layer.

During the initial flow phase, when the spray can penetrate the chain, it has foaming effect.

Better lubrication is obtained after solvent evaporation.

TECHNICAL SPECIFICATIONS

Color	Transparent
Base	Mineral oil
Eu-voc solvent percentage	≈ 39% w/w
Odor	Characteristic
Relative density at 20°C	0,844 g/ml
Steam pressure at 20°C	3 to 4 bar
Yield	2 g/seconds
Temperature resistance	-50°C to +200°C
Drop point	Neutral

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC050101	400	10 years	12	5604630050401

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.