

CHEMISOL METALLIC PAINT

CHEMISOL Metallic Paint is a high-quality and quick-drying spray paint, with metallic effect.



- ✓ **Fast-drying**
- ✓ **Wear resistant**
- ✓ **Resistant to weather influences**
- ✓ **Excellent coverage**

APPLICATIONS

Recommended for wood, metal, glass, stone and different types of plastic.

INDICATIONS

The surface should be clean, dry and degreased.

Must remove old and loose varnish and rust, sand the surface.

For the best metallic effect, apply a layer of white primer.

When it comes to plastic surfaces, apply a layer of plastic primer before applying the white primer. After drying, sand the base coat (grain 600).

The spray must be at room temperature. The best temperature of use is between 15°C and 25°C. Before use, shake the spray can for 2 minutes and spray a sample. The distance to the surface to be treated should be approximately 25 to 30 cm.

INSTRUCTIONS

Apply CHEMISOL Metallic Paint in several thin layers. Before applying the next coat, shake the spray can again.

The metallic effect is reinforced when using a first coat of CHEMISOL Wheel Spray and when applying an acrylic varnish finish coat.



After use, clean the valve (turn the can upside down and press the nozzle for approximately 5 seconds until only gas comes out).

Drying time depends on room temperature, air humidity and thickness of product applied.

TECHNICAL SPECIFICATIONS

Base	Nitrocellulose
EU-VOC solvent percentage	≈ 84% w/w
Solid content	≈ 16% w/w
Coverage	1,25 to 1,75 m ²
Drying	After 5 to 10 minutes
Touch	After 10 to 20 minutes
Hardening	After 2 hours
Temperature resistance	Up to 110°C

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP		ml	Shelf life		EAN
CHC060601	Blue	400	10 years	6	5604630051934
CHC060602	Red	400	10 years	6	5604630051941
CHC060603	Black	400	10 years	6	5604630051958

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.