



## CHEMISOL MULTI SPRAY

**CHEMISOL** Multispray is a universal lubricant that protects metal parts from corrosion and helps to remove rust from oxidised parts.

- ✓ **Good impregnation properties**
- ✓ **Repels moisture**
- ✓ **Removes oil, grease, wax, undercoat and tar**
- ✓ **Cleaning effect**
- ✓ **Prevents corrosion**
- ✓ **Direct spraying**
- ✓ **After cleaning remains a protective coating**

### APPLICATIONS

Recommended for chains liable to light load, fasteners (screws, bolts and nuts), locks, tools, garden tools, machinery, pedals, training devices, roller skates and skateboards. It can be applied on any surface that moves with friction.

### INDICATIONS

The spray must be at room temperature.

The best temperature of use is between 5°C and 30°C.

### INSTRUCTIONS

Before use, shake the spray can. Clean the remaining dirt and grease from the parts before lubricating.

Apply the **CHEMISOL** Multispray in the desired amount.

Once the solvent has evaporated, optimum lubrication is obtained.

## TECHNICAL SPECIFICATIONS

Color	Light Brown Transparent
Base	Mineral oil
Eu-voc solvent percentage	≈ 82% w/w
Odor	Vanilla
Relative density at 20°C	0,80 g/ml
Steam pressure at 20°C	3 to 4 bar
Yield	1,98 g/seconds
Temperature resistance	-50°C to +200°C

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC050102	400	10 years	12	5604630050418

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.