



## CHEMISOL PTFE GREASE SPRAY

CHEMISOL PTFE Grease Spray is a high-quality lubricant, suitable for the treatment of metal and plastic mechanical parts.

- ✓ Exceptional mechanical and thermal stability
- ✓ Excellent adhesion
- ✓ Prevents wear and sticking
- ✓ High viscosity
- ✓ Resistant to weather influences
- ✓ Resistant to weak acids and base
- ✓ Excellent corrosion prevention
- ✓ Water-repellent
- ✓ Direct spraying

### APPLICATIONS

Suitable for metal in metal and plastic connections, roller bearings, sliding bearings, door hinges, ball bearings, springs, stabilization rubbers, shock absorbers and worm wheels.

### INDICATIONS

The spray must be at room temperature.

The best temperature of use is between 5°C and 30°C.

### INSTRUCTIONS

Before use, shake the spray can.

Apply CHEMISOL PTFE Grease Spray in a thin layer.

Once the solvent has evaporated, optimum lubrication is obtained.

## TECHNICAL SPECIFICATIONS

Color	Beige
Base	Mineral Oil with EP Grease
Contains	PTFE (Polytetrafluoroethylene)
Eu-voc solvent percentage	≈ 71% w/w
Odor	Characteristic
Appearance	Greasy
Steam pressure at 20°C	3 to 4 bar
Relative density at 20°C	0,76 g/ml
Yield	1,51 g/seconds
Temperature resistance	-30°C to +160°C
pH	Neutral

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC050104	400	10 years	12	5604630050432

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.