

CHEMISOL PTFE OIL SPRAY

CHEMISOL PTFE Oil Spray is a high-quality lubricant, suitable for the treatment of metal and plastic mechanical parts.



- ✓ **Exceptional mechanical and thermal stability**
- ✓ **Very low friction coefficient**
- ✓ **Excellent adhesion**
- ✓ **Prevents wear and sticking**
- ✓ **Resistant to weather influences**
- ✓ **Resistant to weak acids and base**
- ✓ **Fine structure (particle size 5 micrometres)**
- ✓ **Water-repellent**
- ✓ **Direct spraying**

APPLICATIONS

Recommended for chains, chains, gear wheels, door hinges, industrial vacuum pumps, rails, belts, sliding door guides, fastening systems, (agricultural) machinery and rubber seals.

INDICATIONS

The spray must be at room temperature.

The best temperature of use is between 5°C and 30°C.

INSTRUCTIONS

Before use, shake the spray can.

Apply CHEMISOL PTFE Oil Spray in a thin layer.

After evaporation of the solvent, better lubrication is obtained.

TECHNICAL SPECIFICATIONS

Color	Transparent white
Base	Mineral oil
Eu-voc solvent percentage	≈ 60% w/w
Odor	Characteristic
Steam pressure at 20°C	3 to 4 bar
Yield	1,34 g/seconds
Temperature resistance	-50°C to +250°C
pH	Neutral

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC050103	400	10 years	12	5604630050425

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.