

## CHEMISOL SILICONE SPRAY

**CHEMISOL** Silicone Spray is a high-quality product, suitable for lubricating and protecting plastic and rubber parts.



- ✓ **Excellent adherence**
- ✓ **Water-repellent**
- ✓ **Prevents freezing and drying of rubber parts**
- ✓ **Prevents creaking and squeaking of plastic parts**
- ✓ **Exceptional mechanical and thermal stability**
- ✓ **Resistant to weather influences**
- ✓ **Resistant to weak acids and base**
- ✓ **Direct spraying**

### APPLICATIONS

Recommended for door rubbers, cracked plastic parts, dashboards, bumpers, sunshine roofs, rails (caravans and blinds), sliding doors, saws and mould removal agents.

### INDICATIONS

The spray must be at room temperature.

The best temperature of use is between 5°C and 30°C.

### INSTRUCTIONS



Before use, shake the spray can.

Apply **CHEMISOL** Silicone Spray in a thin layer. After solvent evaporation, optimum lubrication is obtained (approximately 1 minute).

## TECHNICAL SPECIFICATIONS

|                           |                                   |
|---------------------------|-----------------------------------|
| Base                      | Polydimethylsiloxane              |
| EU-VOC solvent percentage | ≈ 88% w/w                         |
| Odor                      | Characteristic                    |
| Relative density at 20°C  | 0,72 g/ml                         |
| Steam pressure at 20°C    | 3 to 4 bar                        |
| Refractive index at 25°C  | 1,403                             |
| Disruptive voltage        | 14 kV/mm at a temperature of 20°C |
| Resistance                | 4 x 10 <sup>15</sup> Ohm/cm       |
| Temperature resistance    | -50°C to +200°C                   |
| pH                        | Neutral                           |

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

| SAP       | ml  | Validade |  |  | EAN           |
|-----------|-----|----------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------|
| CHC050107 | 400 | 10 years | Transparent                                                                         | 12                                                                                    | 5604630050463 |

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.