

CHEMITOOL flap discs comply with European Standards (EN 13743).

ZIRKONIA EXTRA

CHEMITOOL Zirconia Z Flap Disc is excellent for removing accumulated materials on metal and stainless steel surfaces. It has POWERFROST technology to guarantee fast cooling of the disc and the workpiece.

- ✓ **POWERFROST technology**
- ✓ **Conical format**
- ✓ **Aggressive grinding**
- ✓ **Fast cooling**
- ✓ **Great stability and job safety**
- ✓ **Long tool life**

CHEMITOOL Zirconia Z Flap Disc guarantees great durability and stability when polishing materials. The mixture of abrasive grain in Zirconia Alumina Z and semi-friable Aluminium Oxide A provides excellent removal in metal applications.

It is intended to deburr and prepare the weld in carbon steel, mild steel, aluminium, non-ferrous metals and cast iron. Suitable for removing discoloration, material and imperfections on surfaces.

Thanks to its conical format, the CHEMITOOL Zirconia Z Flap Disc has a straight grinding area to eliminate weld beads, chamfering and deburring. To take advantage of the abrasive flap, you should work at a contact angle with the surface from 10° to 25°.

Abrasive















Zirconia Alumina Z and Aluminium Oxide A

Suitable for

Carbon Steel, Mild Steel, Aluminum, Non-Ferrous Metals and Cast Iron

Suitable Machines

Angle Grinder

| SAP | Ø (mm) | Bore Diameter (mm) |  | R.P.M. | Format |  | EAN |
|---------------|--------|--------------------|---|--------|--|---|---------------|
| CHA0209115040 | 115 | 22 | 40 | 13 300 |  | 10 | 5604630058599 |
| CHA0209115060 | 115 | 22 | 60 | 13 300 |  | 10 | 5604630058605 |
| CHA0209115080 | 115 | 22 | 80 | 13 300 |  | 10 | 5604630058612 |
| CHA0209115120 | 115 | 22 | 120 | 13 300 |  | 10 | 5604630058629 |
| CHA0209125040 | 125 | 22 | 40 | 12 200 |  | 10 | 5604630058636 |
| CHA0209125060 | 125 | 22 | 60 | 12 200 |  | 10 | 5604630058643 |
| CHA0209125080 | 125 | 22 | 80 | 12 200 |  | 10 | 5604630058650 |
| CHA0209125120 | 125 | 22 | 120 | 12 200 |  | 10 | 5604630058667 |
| CHA0209180040 | 180 | 22 | 40 | 8 500 |  | 10 | 5604630058674 |
| CHA0209180060 | 180 | 22 | 60 | 8 500 |  | 10 | 5604630058681 |
| CHA0209180080 | 180 | 22 | 80 | 8 500 |  | 10 | 5604630058698 |
| CHA0209180120 | 180 | 22 | 120 | 8 500 |  | 10 | 5604630058704 |

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.