

MMA 150 PRO | MMA 190 PRO

CHEMITOOL MMA 150/190 PRO Inverters are equipment for welding with rutile and basic electrodes, compact, light, and portable with an adjustable strap, allowing you to carry the equipment on your shoulder. They have the Arc Off function to extinguish the arc at an adjustable distance without damaging the part. They have integrated surge protection for a secure connection to generators.

- ✓ Single-Phase power
- ✓ Direct current (DC)
- ✓ Connectable to generators
- ✓ High energy efficiency
- ✓ *HOT START* and *ARC FORCE* devices
- ✓ Thermal protection device
- ✓ MMA 190 PRO with *TIG Lift-Arc*



MMA150PRO

MMA190PRO



DIGITAL



ARC OFF



LOW WEIGH



SINGLE-PHASE



AIR COOLING



MMA CICLE INDICATOR



THERMAL PROTECTION



ENERGY EFFICIENCY

TECHNICAL SPECIFICATIONS

	MMA 150 PRO	MMA 190 PRO
Input voltage	230V (220~240) 50/60Hz	
MMA maximum input current	30,6A	37,8A
TIG maximum input current	-	24,2A
MMA effective input current	11,8A	22,3A
TIG effective input current	-	14,3A
Performance 15% (40°C)	150A	190A
Performance 30% (40°C)	95A	150A
Performance 100% (40°C)	80A	120A
No-load voltage	50V	55 V
Maximum absorbed power	4,9 Kva	9,3 Kva
Thermal isolation	F	
Protection index	IP21	
Efficiency	86%	
Negative and positive connector	10 - 25	35 - 50
Peso	3,5 kg	4,3 kg
Standards	EN60974-1	

INCLUDED ACCESSORIES

MMA 150



ELECTRODE HOLDER



EARTH CLAMP

MMA 190



ELECTRODE HOLDER



EARTH CLAMP

SAP	DESCRIPTION	DIMENSIONS	EAN
CHW0101015000	Inverter MMA 150 PRO	250 x 120 x 195 mm	5604630074780
CHW0101019000	Inverter MMA 190 PRO	320 x 120 x 195 mm	5604630074773

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.