

## COMPACT AND SYNERGIC SEMI AUTOMATIC APPLIANCE 330A



CHEMITOOL Compact and Synergic Semi-Automatic 330A is suitable for use in shipbuilding, fabrication of structures and machinery and production of pipes.


- ✓ High duty cycle
- ✓ Stable wire feed speed
- ✓ Good arc and little spatter
- ✓ Stable and continuous operation



Ø 0.8/1.0



WIRE SPEED  
REGULATOR



THREE-PHASE



AIR COOLING



THERMAL  
PROTECTION



ENERGY  
EFFICIENCY



LOW NOISE

### TECHNICAL SPECIFICATIONS

Voltage	Three-Phase   380V   ±15%
Frequency	50/60 Hz
Input current	16A
Output current	50 – 330A
Output voltage	16,5 - 32A
Duty cycle	60 %
Power factor	0,93
Efficiency	85%
Wire feed speed	2 - 18 m/min
Descent time	1,0 ± 0,5 seconds
Wire diameter	Ø 0,8/1,0 mm
Insulation degree	F
Degree of protection	IP21
Sheet thickness	Above 1.0 mm
Output cable	Above 25 mm <sup>2</sup>
Weight	35 kg

SAP	DESCRIPTION	DIMENSIONS	EAN
CHMIG-330	MIG 330 Semi-Automatic Appliance	780 x 290 x 530 mm	5608907615607

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.