





MMA 120 PRO

CHEMITOOL MMA 120 PRO Inverter is equipment for welding with rutile and basic electrodes, compact, light, and portable with an adjustable strap, allowing you to carry the equipment on your shoulder. It has the Arc Off function to extinguish the arc at an adjustable distance without damaging the part. It has integrated surge protection for a secure connection to generators.

- Single-Phase power
- Direct current (DC)
- Connectable to generators
- High energy efficiency
- HOT START and ARC FORCE devices
- Thermal protection device
- TIG Lift-Arc













LOW WEIGH



SINGLE-PHASE



AIR COOLING



MMA CICLE INDICATOR



THERMAL **PROTECTION**



EFFICIENCY

TECHNICAL SPECIFICATIONS

Input voltage	230V (220V~240V) 50/60 Hz
MMA maximum input current	25A
TIG maximum input current	16A
Performance 40% (40°C)	120A
Performance 60% (40°C)	90A
Performance 100% (40°C)	60A
No-load voltage	62V
Thermal isolation	H (180°)
Maximum absorbed power	7 Kva
Índice de proteção	IP 21
EMC class	В
Efficiency	86%
Negative and positive connector	10 - 25
Peso	2 kg
Standards	EN-60974-1





INCLUDED ACCESSORIES









EARTH CLAMP

ELECTRODE HOLDER

WELDING BRUSH

PROTECTION MASK

SAP	DESCRIPTION	DIMENSIONS	EAN
CHW0101012000	MMA 120 PRO Inverter	210 x 100 x 137	5604630074797

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.