

PLASMA TORCH 80



Power supply	80 A
Duty cycle	60%
Gas	Air
Gas pressure	4,5 – 5,0 bar
Gas flow	160 LPM
Ignition	HF
Post-Flow	80 seconds (recommended)
Length	6 meters
Standard	EN 60974-7

ACCESSORIES

SAP	DESCRIPTION
CHISM0706	CONTACT CUTTING SPACER
CHISM0088	4 POINT SPACER
CHISM0073	SPACER SPRING
CHIVS0665	EXTERNAL NOZZLE
CHIVU0605-10	NOZZLE Ø 1.0MM
CHIVU0605-11	NOZZLE Ø 1.1MM
CHIVU0605-12	NOZZLE Ø 1.2MM
CHIVU0601-10	TIP EXTENSION Ø 1.0MM
CHIVU0601-12	TIP EXTENSION Ø 1.2MM
CHIVF0602	DIFFUSER
CHIVB0604	PLASMA ELECTRODE
CHIZN0510	AIR TUBE
CHIVB0665	PLASMA ELECTRODE EXTENSION
CHIZN0516	AIR TUBE EXTENSION
CHIVZ0690	PLASMA TORCH HEAD
CHIFT0675	SILICONE "O" RING Ø 15.6 x 1.78MM
CHIGV0035	MANUAL PLASMA HANDLE / A SERIES / RED
CHIHJ0722	PROTECTION / PLASMA / YELLOW
CHIHQ0070	TRIGGER
CHIHJ0893	ARTICULATION / SMALL / NEW TYPE
CHIZX0078	SIDE CENTRAL ADAPTER TORCH 5 PINS

SAP	DESCRIPTION	EAN
CHALT81	Plasma Torch 80	5604630055680

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.