



CHEMISOL RUST CONVERTER

CHEMISOL Rust Converter is for protection of metallic parts, against rust. Leaves a layer 30% thicker than a normal paint spray.

- ✓ For exterior use
- ✓ Rust protection
- ✓ Weather resistant

APPLICATIONS

It is suitable for applications in ferrous materials, located outside, and can be applied directly on rust, without anti-rust products.

INDICATIONS

Store the product in a dry place at a temperature below 20°C.

After the first use, it should be kept in a cool, dry place, away from sources of heat.

Avoid direct exposure to sunlight.



INSTRUCTIONS

Shake it before use. Spray the **CHEMISOL** Rust Converter on the surface and let it dry.

TECHNICAL SPECIFICATIONS

Odour	Typical solvent
Relative density, at 20°C	0,75 ÷ 0,80 g/ml
Pressure at 20°C	4,0 ± 0,5 bar
Pressure at 50°C	8,0 ± 0,5 bar
Flash point, under 0°C	Extremely flammable
Residue	17 ± 2%
Opacity	7 to 18 brightness
Brightness	80 to 92 brightness
Dry to touch	20 minutes
Fully dry	24 hours

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP		ml	Shelf Life		EAN
CHC07040001M	Black Mate	400	10 years	6	5604630087193
CHC07040001HG	Black High-Gloss				5604630087209
CHC07040002M	White Mate				5604630087216
CHC07040002HG	White High-Gloss				5604630087223
CHC07040003M	Grey Mate				5604630087230
CHC07040004M	Light Grey Mate				5604630087247
CHC07040005M	Anthracite Mate				5604630087254
CHC07040006M	Green Mate				5604630087261

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.