

INDOORS/OUTDOORS



FLEXIBLE



WEATHER RESISTANT



PAINTABLE



CHEMIACRYL WOOD ACRYLIC SEALANT

CHEMIACRYL Wood Acrylic Sealant has excellent adhesion on all types of natural, lacquered and varnished woods.

- ✓ For indoor and outdoor use
- ✓ Resistant to sunlight
- ✓ High elasticity
- ✓ Paintable, varnish and sand
- ✓ Does not give off odors
- ✓ Does not blacken
- ✓ Ecological

APPLICATIONS

Indicated for countertops, baseboards, parquet, furniture, sealing of carpentry to work and repair wooden structures or furniture. Adheres to lacquered, painted or varnished wood, Pine Wood, Sapelly, Oak, Beech, Cherry and Walnut.

INDICATIONS

To obtain perfect adhesion, the surfaces must be clean and without dust, grease, oil, water or rust. To clean, use organic solvents (alcohol or MEK) until all the dirt is completely removed. Never use soap, detergents or water.

Do not apply the product at temperatures below 5°C.

INSTRUCTIONS

Place the nozzle in the cartridge and cut it according to the desired joint width. With the help of the gun, apply the CHEMIACRYL Wood Acrylic Sealant until the joint is perfectly filled. Then, spread it with a rounded spatula.



Very deep joints must be filled with filling materials, preventing the sealant from sticking to the bottom. Any modification of the joint must be carried out before the drying time of the product.

*transparent packaging for better color perception of the product.

TECHNICAL SPECIFICATIONS

Composition	Acrylic polymers
Appearance	Thixotropic paste
Skin formation at 23°C	Between 30 to 60 minutes
Total product curing time at 23°C	Between 10 to 15 days
Density	1.02 ± 0.2 g / cm ³
Application temperature	from +5 to +35°C
Working temperature resistance	from -15 to +70°C
Shelf Life	48 months

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP		ml		EAN
CHC17010001	White	300	6	5604630086141
CHC17010002	Pine			5604630086158
CHC17010003	Beech			5604630086202
CHC17010004	Oak			5604630086219
CHC17010005	Cherry			5604630086226
CHC17010006	Sapelly			5604630086033
CHC17010007	Walnut			5604630086240
CHC17010008	Wengé			5604630086257
CHC17010009	Black			5604630086264

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.