

## PLASMA TORCH 40



|              |                          |
|--------------|--------------------------|
| Power supply | 40 A                     |
| Duty cycle   | 60%                      |
| Gas          | Air                      |
| Gas pressure | 4,5 – 5,0 bar            |
| Gas flow     | 160 LPM                  |
| Ignition     | HF                       |
| Post-Flow    | 80 seconds (recommended) |
| Length       | 6 meters                 |
| Standard     | EN 60974-7               |

## ACCESSORIES

| SAP         | DESCRIPTION                   |
|-------------|-------------------------------|
| CHIVS0076   | EXTERNAL NOZZLE               |
| CHVU0680-10 | TIP                           |
| CHIVB0086   | ELECTRODE                     |
| CHIVZ0031   | PLASMA TORCH HEAD             |
| CHIHJ0724   | TRIGGER                       |
| CHIGV0025   | HANDLE                        |
| CHIHJ0860   | SMALL JOINT TIG9-17-20        |
| CHIHJ0868   | LARGE SUPPORT SPRING TIG18-26 |
| CHIVN0612   | CABLE ASSEMBLY / 55 SG / 5M   |
| CHIHQ0757   | 2 HOLES CONNECTOR             |
| CHIHJ0029   | PROTECTIVE NUT CH19           |

| SAP    | DESCRIPTION     | EAN           |
|--------|-----------------|---------------|
| CHSG55 | Plasma Torch 40 | 5608907541289 |

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.