

**CHEMISOL ANTI-SPATTER WELDING SPRAY**

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier**

Code: **CHC050109**  
Product name: **CHEMISOL ANTI-SPATTER WELDING SPRAY**  
UFI: **MK20-40AR-5006-H95F**

**1.2. Relevant identified uses of the substance or mixture and uses advised against**Intended use: **Anti-adhesive for welding.**

Identified Uses	Industrial	Professional	Consumer
Consumer	-	-	✓
Industrial Use	✓	-	-
Professional Use	-	✓	-

**1.3. Details of the supplier of the safety data sheet**

Name: **LUSAVOUGA – Máquinas e Acessórios Industriais, S.A.**  
Full address: **Edifício Lusavouga  
Avenida Europa, 375  
3800-533 Cacia  
Portugal**  
tel. **+351 234 915 010**  
fax **+351 234 915 015**  
e-mail address of the competent person responsible for the Safety Data Sheet: **qualidade@lusavouga.pt**

**1.4. Emergency telephone number**

For urgent inquiries refer to:  
**GB - National Poisons Information Service (NPIS) Tel. 0344 892 0111 (United Kingdom)**  
**Members of the Public: NHS 111 (England), NHS 24 (Scotland) or NHS Direct (Wales)**  
**USA - American Association of Poison Control Centers: Tel. 1 800 222 1222 (U.S.A.)**

### SECTION 2. Hazards identification

**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL****2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

**H222** Extremely flammable aerosol.  
**H229** Pressurised container: may burst if heated.

Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P251** Do not pierce or burn, even after use.  
**P410+P412** Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.  
**P211** Do not spray on an open flame or other ignition source.  
**P102** Keep out of reach of children.

Statements on the aspiration toxicity classification were not included in the label elements, based on section 1.3.3. of Annex I to CLP.

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>Propane</b>		
CAS 74-98-6	$55 \leq x < 59$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note/notes according to Annex VI to the CLP Regulation: U
EC 200-827-9		
INDEX 601-003-00-5		
Reg. no. 01-2119486944-21-0046		
<b>Butane</b>		
CAS 106-97-8	$23 \leq x < 27$	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note/notes according to Annex VI to the CLP Regulation: C U

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL**

EC 203-448-7

INDEX 601-004-00-0

Reg. no. 01-2119474691-32-XXXX

**Benzene, mono-C10-13-alkyl  
derivs., Distn. residues**

CAS 84961-70-6

 $11 \leq x < 15$ 

Asp. Tox. 1 H304

EC 284-660-7

INDEX -

Reg. no. 01-2119485843-26-0008

**Isobutane**

CAS 75-28-5

 $3 \leq x < 5$ 

Flam. Gas 1A H220, Press. Gas H280

EC 200-857-2

INDEX 601-004-00-0

Reg. no. 01-2119485395-27-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 88,00 %

**SECTION 4. First aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

**5.2. Special hazards arising from the substance or mixture**

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL****5.3. Advice for firefighters**

## GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

## SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

**6.2. Environmental precautions**

Do not disperse in the environment.

**6.3. Methods and material for containment and cleaning up**

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

DEU Deutschland TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte



**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL**

Oral	NPI			230 µg/kg bw/day				
Inhalation	NPI	NPI	NPI	1,6 mg/m <sup>3</sup>	NPI	NPI	NPI	3,2 mg/m <sup>3</sup>
Skin	NPI	NPI	NPI	2,2 mg/kg bw/d	NPI	NPI	NPI	4,3 mg/kg bw/d

**Isobutane  
Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m <sup>3</sup>	ppm	

TLV-ACGIH			800	
-----------	--	--	-----	--

**Diisononyl phthalate  
Threshold Limit Value**

Type	Country	TWA/8h	STEL/15min	Remarks / Observations
		mg/m <sup>3</sup>	ppm	

WEL	GBR	5		
-----	-----	---	--	--

**Predicted no-effect concentration - PNEC**

Normal value for the terrestrial compartment	30	mg/kg/d
----------------------------------------------	----	---------

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				4,4 mg/kg bw/d				
Inhalation				15,3 mg/m <sup>3</sup>				51,72 mg/m <sup>3</sup>
Skin				220 mg/kg bw/d				366 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

**HAND PROTECTION**

None required.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL**

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Colour	straw yellow
Odour	odourless
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	< 0 °C
Evaporation Rate	Not available
Flammability of solids and gases	flammable gas
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,54 ÷ 0,58 g/ml a 20°C
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	not applicable
Oxidising properties	not applicable

**9.2. Other information**

VOC (Directive 2010/75/EC) :	88,24 % - 494,14 g/litre
Self-ignition temperature	> 400 °C base liquida
Flash point	160 - 180 °C base liquida

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL****SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

**10.4. Conditions to avoid**

Avoid overheating.

**10.5. Incompatible materials**

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

**10.6. Hazardous decomposition products**

Information not available

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY



**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL**

ATE (Inhalation) of the mixture:  
Not classified (no significant component)  
ATE (Oral) of the mixture:  
Not classified (no significant component)  
ATE (Dermal) of the mixture:  
Not classified (no significant component)

**Butane**

LC50 (Inhalation) > 1442,738 mg/l/15min rat

**Propane**

LC50 (Inhalation) 800000 ppm 15 min

**Isobutane**

LC50 (Inhalation) > 1442,738 mg/l/15min rat

Benzene, mono-C10-13-alkyl derivs., distn. residues

LD50 (Oral) > 2000 mg/kg rat

LD50 (Dermal) > 2000 mg/kg rat

**SKIN CORROSION / IRRITATION**

Does not meet the classification criteria for this hazard class

**SERIOUS EYE DAMAGE / IRRITATION**

Does not meet the classification criteria for this hazard class

**RESPIRATORY OR SKIN SENSITISATION**

Does not meet the classification criteria for this hazard class

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL**STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

**SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

Butane  
LC50 - for Fish > 24,11 mg/l/96h

Propane  
LC50 - for Fish 85,82 mg/l/96h  
EC50 - for Crustacea 41,82 mg/l/48h

Isobutane  
LC50 - for Fish > 24,11 mg/l/96h

Benzene, mono-C10-13-alkyl derivs., distn. residues  
EC50 - for Crustacea 1,4 mg/l/48h  
Chronic NOEC for Crustacea 1,4 mg/l 48 h  
Chronic NOEC for Algae / Aquatic Plants 2,08 mg/l 72 h

**12.2. Persistence and degradability**

Propane  
Global Warming Potential (GWP): 3. Ozone Depletion Potential (ODP): 0.

Butane  
Solubility in water 0,1 - 100 mg/l  
Rapidly degradable

Propane  
Solubility in water 0,1 - 100 mg/l  
Rapidly degradable

Isobutane  
Rapidly degradable

Benzene, mono-C10-13-alkyl derivs., distn.

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL**

residues  
NOT rapidly degradable

**12.3. Bioaccumulative potential**

Butane  
Partition coefficient: n-octanol/water 1,09

Propane  
Partition coefficient: n-octanol/water 1,09

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Product residues are to be considered special hazardous waste.

Empty cans, even if completely emptied, must not be dispersed in the environment.

The aerosol container overheated to a temperature above 50Å ° C can burst even if it contains a small residue of gas.

Disposal must take place in an authorized place and in compliance with the laws in force.

Waste transportation can be subject to ADR.

European waste catalog number (contaminated containers):

The aerosol as domestic waste is excluded from the application of the aforementioned standard.

The exhausted aerosol for professional / industrial use can be classified:

15.01.10 \*: packaging containing residues of dangerous substances or contaminated by these substances.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL**

**SECTION 14. Transport information**

**14.1. UN number**

ADR / RID, IMDG, IATA: 1950

**14.2. UN proper shipping name**

ADR / RID: AEROSOLS  
IMDG: AEROSOLS  
IATA: AEROSOLS, FLAMMABLE

**14.3. Transport hazard class(es)**

ADR / RID: Class: 2 Label: 2.1  
IMDG: Class: 2 Label: 2.1  
IATA: Class: 2 Label: 2.1



**14.4. Packing group**

ADR / RID, IMDG, IATA: -

**14.5. Environmental hazards**

ADR / RID: NO  
IMDG: NO  
IATA: NO

**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	Special Provision: - EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A145, A167, A802	

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL****14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product

Point 40

Contained substance

Point	52	Diisononyl phthalate Reg. no.: 01- 2119430798-28- XXXX
-------	----	-----------------------------------------------------------------

Substances in Candidate List (Art. 59 REACH)On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL****SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Gas 1A</b>	Flammable gas, category 1A
<b>Aerosol 1</b>	Aerosol, category 1
<b>Aerosol 3</b>	Aerosol, category 3
<b>Press. Gas (Liq.)</b>	Liquefied gas
<b>Press. Gas</b>	Pressurised gas
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>H220</b>	Extremely flammable gas.
<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H280</b>	Contains gas under pressure; may burst if heated.
<b>H304</b>	May be fatal if swallowed and enters airways.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**W506/LUSA - CHEMISOL WELDING ANTI-SPATTER 400 ml  
CHEMITOOL****GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition

- Handling Chemical Safety

- INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

- IFA GESTIS website

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

**Changes to previous review:**

The following sections were modified:

01 / 08 / 13.