

## CHEMISOL VASELINE SPRAY

CHEMISOL Vaseline Spray lubricates, cleans and protects mechanisms and electrical parts that require periodic maintenance, cleaning and lubrication.

- ✓ **Excellent adhesion**
- ✓ **It does not harden overtime**
- ✓ **Resistant to climate**
- ✓ **Corrosion prevention**



### APPLICATIONS

Suitable for electrical parts. For lubricating delicate mechanisms and protect electric components (terminals and connectors).

### INDICATIONS

Store the product in a dry location and don't store it with a temperature under 0°C and over 45°C. After the first usage, conserve in a fresh and dry location, away from heating sources.


### INSTRUCTIONS

Shake and spray directly on the surface from a distance of 15-25 cm. The product could also be used with a straw that is attached to the cap.

### TECHNICAL SPECIFICATIONS

Color	Transparent
Odour	Characteristic of solvent
Relative density at 20°C	0,63 ÷ 0,67 g/ml
Flash point under 0°C	Extremely flammable
Pressure at 20°C	4/6 bar
Penetration at 25°	ASTM D 937 mm / 10 160 ÷ 200
Drip point	ASTM D 127°C 52 ÷ 60
Viscosity at 100°	6,5 ÷ 8 mm <sup>2</sup> /s
Kinematic viscosity at 100°C	5 - 9 mm <sup>2</sup> /s

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC040105	400	10 years	12	5604630050395

**Note:** The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.