

CHEMISOL ANTI-SPATTER WELDING SPRAY

CHEMISOL Anti-Spatter Welding Spray is designed to prevent particles projected by welding from damaging the surfaces to be welded, at the welding point and in the surrounding area.



- ✓ **Non-flammable**
- ✓ **Silicone-free**
- ✓ **Non-corrosive**
- ✓ **Slightly basic**
- ✓ **Can be removed with water**

APPLICATIONS

Recommended for welding devices and welding areas. It is suitable for autogenous, electric and inert-gas welding.

INDICATIONS

Store the product in a dry location and don't store it at a temperature under 0°C and over 45°C. After the first usage, conserve in a fresh and dry location, away from heating sources.

INSTRUCTIONS

Before applying, clean the torch and apply the product. Spray onto the mouth of the torch and the surface edges to be welded. Do not spray directly on the flaps to be welded. Shake well before use. Hold the can 20-30 cm away from the surface and in a vertical position. Do not spray excessive amounts of product.





TECHNICAL SPECIFICATIONS

Odour	Typical of solvent
Relative density at 20°C	0,55 ÷ 0,59 g/ml
Flash point under 0°C	Extremely flammable
Pressure at 20°C	3/5 bar
Vapor pressure at 20°C	<0,01 hPa
Vapor density (air=1)	9 - 12
Viscosity at 50°C (ASTM D 445)	11 ÷ 24 cst
Solubility	Insoluble in water
Autoignition temperature (dry residual)	> 400°C
Corrosion on copper (ASTM D 130)	1

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.



SAP	ml	Shelf Life			EAN
CHC050109	400	10 years	Straw yellow	12	5604630050470

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.