Page 1/8



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 60

Revision: 02.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: <u>CHEMISOL STAINLESS STEEL</u>

· Article number: CHC030105

• 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture Preparation

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: LUSAVOUGA, S.A. Edificio Lusavouga - Avenida Europa, 375 3800 - 533 CACIA Aveiro (Portugal) +351 234 915 010 | +351 234 915 015 lusavouga@lusavouga.pt | www.lusavouga.com

• Further information obtainable from: Quality Department - qualidade@lusavouga.pt • 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Flam. Aerosol 1 GHS07 STOT SE 3 H336 May cause drowsiness or dizziness. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · Classification according to Directive 67/548/EEC or Directive 1999/45/EC *F+; Extremely flammable R12*: Extremely flammable. *R52/53-66-67*: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. · Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurised container. Has a narcotising effect. Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

GB

Page 2/8


Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 60

Revision: 02.06.2015

Trade name: CHEMISOL STAINLESS STEEL



Dangerous components:		
CAS: 64742-48-9 EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx		25-50%
CAS: 109-66-0	♦ Asp. Tox. 1, H304	20-25%
EINECS: 203-692-4	pentane Xn R65	20-23%
Index number: 601-006-00-1	F + R12	
Reg.nr.: 01-2119459286-30-xxxx		
	R66-67	
	(b) Flam. Liq. 2, H225	
	& Asp. Tox. 1, H304 Aquatic Chronic 2, H411	
	STOT SE 3, H336	

GB

Printing date 02.06.2015

Version number 60

Revision: 02.06.2015

Trade name: CHEMISOL STAINLESS STEEL

	(Co	ntd. of page 2)
CAS: 74-98-6	propane	10-12.5%
EINECS: 200-827-9	<i>F</i> + <i>R</i> 12	
Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	🚸 Flam. Gas 1, H220 Press. Gas C, H280	
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280	5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280	5-10%
Additional information. For the	wording of the listed risk phrases refer to section 16	

· Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

Keep away from ignition sources.

• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 60

Revision: 02.06.2015

Trade name: CHEMISOL STAINLESS STEEL

(Contd. of page 3) · Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use. · 7.2 Conditions for safe storage, including any incompatibilities · Storage: • Requirements to be met by storerooms and receptacles: Store in a cool location. Observe official regulations on storing packagings with pressurised containers. · Information about storage in one common storage facility: Not required. · Further information about storage conditions: Protect from heat and direct sunlight. · 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection · Additional information about design of technical facilities: No further data; see item 7. · 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 109-66-0 pentane WEL Long-term value: 1800 mg/m³, 600 ppm 106-97-8 butane WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Personal protective equipment: • General protective and hygienic measures: Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. · Respiratory protection: Not required. · Protection of hands: Not required. · Material of gloves Not required. · Penetration time of glove material Not required. · Eye protection: Not required. **SECTION 9: Physical and chemical properties** · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Aerosol Colour: According to product specification **Characteristic** · Odour: · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition *Melting point/Melting range:* Undetermined.

(Contd. on page 5)

GB

Printing date 02.06.2015

Version number 60

Revision: 02.06.2015

Trade name: CHEMISOL STAINLESS STEEL

	(Contd. of page
Boiling point/Boiling range:	Not applicable, as aerosol.
· Flash point:	< 0 °C (< 32 °F)
-	Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	> 200 °C (> 392 °F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.</i>
Explosion limits:	
Lower:	0.6 Vol %
Upper:	10.9 Vol %
• Vapour pressure at 20 •C (68 •F):	3500 hPa (2625 mm Hg)
• Density at 20 •C (68 •F):	0.683 g/cm ³ (5.7 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	92.4 %
EU-VOC:	631.4 g/l
• EU-VOC in %:	92.44 %
Solids content:	14.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

64742-48-9 Naphta (petroleum), hydrotreated heavy

Oral LD50 >15000 mg/kg (rat)

(Contd. on page 6) GB

Printing date 02.06.2015

Version number 60

Revision: 02.06.2015

Trade name: CHEMISOL STAINLESS STEEL

		(Contd. of page 5)
Dermal	LD50	>3000 mg/kg (rab)
Inhalative	LC50 / 4 h	>2.8 mg/m3 (rat)
109-66-0 p	entane	
Oral	LD50	>16000 mg/kg (rat)
		>2500 mg/kg (rat)
		>5000 mg/kg (rabbit) >100 mg/m3 (rat)
Inhalative	LC50 / 4 h	>100 mg/m3 (rat)
106-97-8 b	outane	
Inhalative	LC50/4 h	658000 mg/m3 (rat)

· Primary irritant effect:

· Skin corrosion/irritation No irritant effect.

· Serious eye damage/irritation No irritating effect.

· Respiratory or skin sensitisation No sensitising effects known.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

64742-48-9 Naphta (petroleum), hydrotreated heavy

LC50 / 96 h >100 mg/l (crustacean (amphipod))

>100 mg/l (fish)

109-66-0 pentane

EC50 / 48 h 9.7 mg/l (daphnia magna)

LC50 / 96 h 1-10 mg/l (fish)

· 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

• 12.5 Results of PBT and vPvB assessment

- *PBT*: Not applicable. • *vPvB*: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

\cdot European waste catalogue

14 06 03* other solvents and solvent mixtures

15 01 04 metallic packaging

(Contd. on page 7)

Page 7/8

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 60

Revision: 02.06.2015

(Contd. of page 6)

Trade name: CHEMISOL STAINLESS STEEL

· Uncleaned packaging:

• Recommendation: Non contaminated packagings may be recycled.

SECTION 14: Transport information		
14.1 UN-Number		
ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
Class	2 5F Gases.	
Label	2.1	
IMDG, IATA		
Class	2.1	
Label	2.1	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Warning: Gases.	
Danger code (Kemler):	-	
EMS Number:	F- D , S - U	
14.7 Transport in bulk according to Anne	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		_
ADR		
Limited quantities (LQ)	1L	
Excepted quantities $(\widetilde{E}Q)$	Code: E0	
	Not permitted as Excepted Quantity	
Transport category	2	
Tunnel restriction code	<i>D</i>	
IMDG		
Limited quantities (LQ)	lL	
Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
UN "Model Regulation":	UN1950, AEROSOLS, 2.1	

(Contd. on page 8)

Printing date 02.06.2015

Version number 60

Revision: 02.06.2015

Trade name: CHEMISOL STAINLESS STEEL

(Contd. of page 7)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- *R12 Extremely flammable.*

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- *R65 Harmful: may cause lung damage if swallowed.*
- *R66 Repeated exposure may cause skin dryness or cracking.*
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: Quality Department
- · Contact: qualidade@lusavouga.pt
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

- Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Gas 1: Flammable gases, Hazard Category 1
- Flam. Aerosol 1: Flammable aerosols, Hazard Category 1 Press. Gas C: Gases under pressure: Compressed gas
- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- STOT SE 3: Specific target organ toxicity Single exposure, Hazard Category 3
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment Chronic Hazard, Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment Chronic Hazard, Category 3
- \cdot * Data compared to the previous version altered.