

Page 1/10

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version number 68

Revision: 11.03.2020

	Taentificatio	on of the substance/mixture and of the company/undertaking
· 1.1 Product iden	ntifier	
· Trade name: <u>C</u>	HEMISOL IM	PREGNATION SPRAY
No further relev • Sector of Use SU21 Consume SU22 Professie craftsmen) • Product categor • Process categor PROC7 Indust PROC11 Non	e ntified uses of ant information er uses: Private onal uses: Publ ry PC34 Textil y rial spraying industrial spray	e households / general public / consumers lic domain (administration, education, entertainment, services, le dyes, and impregnating products ying
		the mixture Preparation
Manufacturer/S LUSAVOUGA, Edifício Lusavou 3800 - 533 CAC Aveiro (Portuga +351 234 915 0	S upplier: S.A. 19ga - Avenida E 17 1) 10 +351 234 9	
•	0 1 1	
 Further inform 1.4 Emergency +31 (0)561-694 	telephone num	
		formation Centre Tel: +44 0344 892 0111
SECTION 2:	Hazards ide	entification
		·
 2.1 Classification Classification a 		unce or mixture gulation (EC) No 1272/2008
flame	_	
Aerosol 1	H222-H229	9 Extremely flammable aerosol. Pressurised container: May burst if heated.
envire	onment	
Aquatic Chronic	e 2 H411	Toxic to aquatic life with long lasting effects.
\mathbf{V}		
Skin Innit 2	H215	Causes skin irritation
Skin Irrit. 2 Eye Irrit. 2	H315 H319	Causes skin irritation. Causes serious eye irritation.

Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version number 68

Revision: 11.03.2020

GB

Trade name: CHEMISOL IMPREGNATION SPRAY

STOT SE 3	H336	(Contd. of page May cause drowsiness or dizziness.
		may cause arousiness or alliness.
2.2 Label el		
		lation (EC) No 1272/2008
		labelled according to the CLP regulation.
Hazard pice	ograms	
$\mathbf{\wedge}$	\land	
$\langle \psi \rangle$	↓ ↓ ↓ ↓ 2	
	\checkmark	
GHS02	GHS07 GHS09	
011502	011507 011503	
Signal word	1 Danger	
-		
		ents of labelling:
		anes, isoalkanes, cyclics, <5% n-hexane
propan-2-o		
n-butyl acer		
Hazard stat		
H222-H229		able aerosol. Pressurised container: May burst if heated.
H315	Causes skin irrit	
H319	Causes serious e	
H336		siness or dizziness.
H411		life with long lasting effects.
	ary statements	
P101		e is needed, have product container or label at hand.
P102	Keep out of reac	
P210		heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211		an open flame or other ignition source.
P251	*	burn, even after use.
P260	Do not breathe s	
		light. Do not expose to temperatures exceeding 50 °C/122 °F.
P501		nts / container in accordance with regional regulations.
	information:	
	<u>^</u>	possible without sufficient ventilation.
2.3 Other h		
	PBT and vPvB ass	sessment
PBT: Not a		
vPvB: Not a	applicable.	

SECTION 3: Composition/information on ingredien

· 3.2 Chemical characterisation: Mixtures

*

· Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components: EC number: 921-024-6 Reg.nr.: 01-2119475514-35 * Flam. Liq. 2, H225 Asp. Tox. 1, H304 * Aquatic Chronic 2, H411 * Skin Irrit. 2, H315; STOT SE 3, H336

Printing date 12.02.2021

Version number 68

Revision: 11.03.2020

Trade name: CHEMISOL IMPREGNATION SPRAY

		Contd. of page 2)
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	12.5-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	2.5-<5%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- *After swallowing:* Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Keep away from ignition sources.
 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3** *Methods and material for containment and cleaning up:* Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

(Contd. on page 4)

GB

Printing date 12.02.2021

Version number 68

Revision: 11.03.2020

Trade name: CHEMISOL IMPREGNATION SPRAY

· 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
• Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- **Requirements to be met by storerooms and receptacles:** Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 2 B

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.
- *Immediately remove all soiled and contaminated clothing*
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin. Avoid contact with the eyes.
- **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

(Contd. on page 5)

(Contd. of page 3)

Printing date 12.02.2021

Version number 68

Revision: 11.03.2020

(Contd. of page 4)

Trade name: CHEMISOL IMPREGNATION SPRAY

· Protection of hands:



Protective gloves

· Material of gloves Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

• Eye protection:



Tightly sealed goggles

9.1 Information on basic physical and	l chemical properties	
General Information		
Appearance:		
Form:	Aerosol	
Colour:	Light yellow	
Odour:	Solvent-like	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling ran	ge: Not applicable, as aerosol.	
Flash point:	Not applicable, as aerosol.	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	>200 °C (>392 °F)	
Decomposition temperature:	Not determined.	
Explosive properties:	Not determined.	
Explosion limits:		
Lower:	0.6 Vol %	
Upper:	12 Vol %	
Vapour pressure at 20 °C (68 °F):	3500 hPa (2625.2 mm Hg)	
Density at 20 °C (68 °F):	0.7 g/cm ³ (5.8 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	

GB

Printing date 12.02.2021

Version number 68

Revision: 11.03.2020

Trade name: CHEMISOL IMPREGNATION SPRAY

		(Contd. of page 5
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	98.7 %	
VOC (EC)		
	659.6 g/l	
· VOC-EU%	98.75 %	
· Solids content:	1.3 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

×

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values relev	ant for classification:
Hydrocarb	ons, C6-C7	, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rab)
Inhalative	LC50 / 4h	>25.2 mg/l (rat)
67-63-0 pr	opan-2-ol	
Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50	>25 mg/l (rat)
		LC 50: 6h
123-86-4 n	-butyl aceta	ate
Oral	LD50	10800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21 mg/m3 (rat)
· Primary ir	ritant effect	
· Skin corro	sion/irritati	on
Causes ski	n irritation.	
· Serious ey	0	
	ious eye irri	itation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB

Printing date 12.02.2021

Version number 68

Revision: 11.03.2020

(Contd. of page 6)

Trade name: CHEMISOL IMPREGNATION SPRAY

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50 / 48 h 3 mg/l (daphnia magna)

EC50 / 72 h 30-100 mg/l (algae)

LC50/96 h 11.4 mg/l (fish)

67-63-0 propan-2-ol

LC50/96h 9640 mg/l (pimephales promelas; 96h)

- LC50 / 24 h 9714 mg/l (daphnia magna)
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Also poisonous for fish and plankton in water bodies.
- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

SECTION 14	1: Transpor	t information

· 14.1 UN-Number · ADR, IMDG, IATA

UN1950

(Contd. on page 8)

Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version number 68

Revision: 11.03.2020

	(Contd. of page
· 14.2 UN proper shipping name · ADR · IMDG	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (Naphtha (petroleum), hydrotreated light), MARINE POLLUTANT
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
ADR	
· Class	2 5F Gases.
· Label	2.1
· Class	2.1
· Label · IATA	2.1
· Class · Label	2.1 2.1
	2.1
· 14.4 Packing group · ADR, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	
· Marine pollutant: · Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
 14.6 Special precautions for user Hazard identification number (Kemler code): 	Warning: Gases.
· EMS Number:	F-D,S-U
• Stowage Code • Segregation Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre
	Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

(Contd. on page 9) GB

Printing date 12.02.2021

Version number 68

Revision: 11.03.2020

Trade name: CHEMISOL IMPREGNATION SPRAY

	(Contd. of page 8
· Transport/Additional information:	
· ADR	
\cdot Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
• Transport category	2
• Tunnel restriction code	D
·IMDG	
\cdot Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- P3a FLAMMABLE AEROSOLS
- E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57
- None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated. H304
May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Quality Department

• Contact: qualidade@lusavouga.pt

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.02.2021

Version number 68

Revision: 11.03.2020

Trade name: CHEMISOL IMPREGNATION SPRAY

(Contd. o	f page 9)
· Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerni	ng the
International Transport of Dangerous Goods by Rail)	
ICAO: International Civil Aviation Organisation	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the	
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
SVHC: Substances of Very High Concern	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1A: Flammable gases – Category 1A	
Aerosol 1: Aerosols – Category 1	
Press. Gas (Comp.): Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
• * Data compared to the previous version altered.	
	GB