

CHEMISOL PAINT REMOVER

CHEMISOL Paint Remover is ideal for industrial or domestic use, "do-it-yourself" to remove any type of paint of various types of materials.

- ✓ Removes paint
- ✓ For all types of materials
- ✓ Leaves no residue
- ✓ Highly thixotropic

APPLICATIONS

It can be used on different materials, metal and wood surfaces as well as other materials such as glass and polyethylene.

INDICATIONS

Store the product in a dry location and don't store it at a temperature under 0°C and over 45°C.

After the first usage, conserve in a fresh and dry location, away from heating sources.

Avoid use on warm surfaces or exposed to the sun.

INSTRUCTIONS


Shake well before use. Apply a rich layer of CHEMISOL Paint Removal. Wait for the complete penetration of the product, after remove everything with a spatula or with a cloth.



TECHNICAL SPECIFICATIONS

Color	Colorless
Odour	Characteristic of solvent
Relative density at 20°C	0,74 ÷ 0,78 g/ml
Flash point, under 0°C	Extremely flammable
Pressure at 20°C	4/6 bar
Initial boiling point (dry residue)	> 35°C
Vapor density (dry residue)	> 1
Viscosity (dry residue)	120,0 cp – 250,0 cp IST 524
Solubility	Insoluble in water

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC030107	400	10 years	12	5604630059282

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.