



BLOW TORCH FOR WELDING

Blow Torch for Welding **CHEMITOOL** is suitable for welding works.

- ✓ **Capacity: 0,5mm-3mm (1/64" - 1/8")**
- ✓ **Connections: BSP 1/4" - R.H., BSP3/8" - L.H.**

TECHNICAL SPECIFICATIONS

Tips	Opening	Welding capacity	Oxygen pressure	Acetylene pressure
100	Ø 0,9 m/m	0,5~1 m/m	1,5 Kg/cm ²	0,2~0,5 Kg/cm ²
160	Ø 1 m/m	1~1,5 m/m	1,5 Kg/cm ²	0,2~0,5 Kg/cm ²
250	Ø 1,1 m/m	1,5~2 m/m	2 Kg/cm ²	0,2~0,5 Kg/cm ²
315	Ø 1,2 m/m	2~2,5 m/m	2,5 Kg/cm ²	0,2~0,5 Kg/cm ²
400	Ø 1,5 m/m	2,5~3 m/m	2,5 Kg/cm ²	0,2~0,5 Kg/cm ²

SAP	Description	Weight	EAN
CHAW-501	Blow Torch for Welding	0,565 Kg	5608907261897

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.