



FALL PROTECTION KIT

Fall Protection Kit **CHEMITOOL** indicated for works in which there is a risk of falling composed of a harness that has a dorsal fall arrest point and a polyamide lanyard with 1,5m that ends with steel connectors and with an automatic threaded locking system. The lifetime estimated of this product is 10 years and 5 years after the first use.

- ✓ **Harness with 8 mm steel D buckle**
- ✓ **Harness with a dorsal fall arrest point**
- ✓ **Harness with adjustable buckles on legs**
- ✓ **Polyamide lanyard with a diameter of 14mm**
- ✓ **Steel directional connectors**
- ✓ **Connectors with an automatic threaded locking system**



EN 361:2002
(FALL ARREST HARNESS)



EN 354:2010
(LANYARD)

TECHNICAL SPECIFICATIONS

HARNESS COMPOSITION	45 MM POLYESTER STRAP	
LANYARD COMPOSITION	THREE-STRAND TWISTED POLYAMIDE ROPE, STEEL CONNECTORS	
Harness color	Orange	
Harness size	One Size	
Lanyard size	1,5 m	
Connectors Minimum Breaking Load	22 kN	
Connectors Opening Diameter	18 mm	
Harness Weight	0,5700 Kg	
Lanyard Weight	0,672 kg	
Certificação CE	Harness norm: - EN 361:2002 Health and safety requirements of R.D. 1407/1992 Control body nº 1019 Certificate nº 1019-036/Q/2013	Lanyard norm: - EN 354:2010 Regulation (UE) 2016/425 Control body nº 0321

SAP	COMPOSITION	EAN
CHS09010103	1 Fall Protection Harness and 1 Lanyard	5604630103886

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.