



CHEMISOL CONTACT CLEANER SPRAY

CHEMISOL Contact Cleaner Spray is a high-quality product suitable for cleaning electric contacts, with highly solvent properties.

- ✓ **Strong spraying**
- ✓ **Excellent dissolving properties**
- ✓ **Does not damage plastics or rubbers**
- ✓ **Does not leave residues**
- ✓ **Non-corrosive**

APPLICATIONS

Recommended for switches, batteries, contact points, printed circuit board switches and multiple sockets.

INDICATIONS

The spray must be at room temperature.

The best temperature of use should be from 5°C to 30°C.

INSTRUCTIONS


Before use, shake the spray can.

- 1° Switch off electrical installations before treatment;
- 2° Spray the parts to be treated until the contamination has disappeared;
- 3° Turn on the electrical installation only after solvent evaporation (minimum 15 minutes).

TECHNICAL SPECIFICATIONS

Color	Transparent
Base	Surfactant solution
Propellant	Carbon dioxide (CO ₂)
EU-VOC solvent percentage	≈ 97% w/w
Odor	Characteristic
Relative density at 20°C	0,73 g/ml
Yield	3,8 g/seconds
Steam pressure at 20°C	5,5 to 6,5 bar
Refractive index at 25°C	≈ 4 m ²

These values may vary depending on environmental factors such as temperature and humidity. The curing time is higher the lower the temperature and humidity and the greater the thickness of the product.

SAP	ml	Shelf Life		EAN
CHC030103	400	10 years	12	5604630050326

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.