



POLYAMIDE ROPE

CHEMITOOL Polyamide Rope semi static with 14mm diameter and three lengths available: 10m; 1.5m and 20m. The ends are in PVC to protect the rope from the wear caused by the connectors. For vertical use with EN 353-2 fall arrest devices appropriate to the diameter of this rope

- ✓ **Breaking force: 4000 kg**
- ✓ **Diameter: 14 mm**
- ✓ **Elongation: 500 daN 23% - 1000 daN 33% - 1500 daN 39% - 2000 daN 43%**



EN 353-2:2002

TECHNICAL SPECIFICATIONS

COMPOSITION	3 POLYAMIDE CAPE
Finishing	Loop and terminal knot or thimble at the ends
Color	White and Red
Diameter	14 mm
Breaking force	4000 kg
Elongation	500 daN 23% 1000 daN 33% 1500 daN 39% 2000 daN 43%
Sizes	10 M; 1,5 M and 20M
CE Certification	Norm: - EN 353-2:2002 Regulation (UE) 2016/425 Control body n° 1019

SAP	SIZES	EAN
CHS09030101	10 M	5604630103893
CHS09030102	1,5 M	5604630103909
CHS09030105	20M	5604630128063

Note: The technical information provided, either verbally or in writing, is based on our current knowledge and should be considered as collaboration without commitment. The use of the product is beyond our control, thus, we rule out any responsibility for its improper use. The customer is responsible to confirm and validate (by testing) if the product is suitable for the process and the type of use in question. Our purpose is exclusively to guarantee the quality of the products, according to our standards.