

IDENTIFICATION:	CH040X
EDITION:	Fev 2022
VERSION:	6

INGLÉS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Nº DOP_CH040_2015_04

1. Unique identification code of the product-type:

SEAL&BOND PU 40 CHEMIPOL

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for non-structural use in joints in buildings for exterior and in accordance with the European standard EN 15651-1 (F EXT-INT CC)

Sealant for indoor and outdoor pedestrian walkways (suitable for use in cold climates) in accordance with the European standard EN 15651-4 (PW EXT INT CC)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

CHEMITOOL®
Avenida Europa, 375
3800-533 Cacia – Portugal

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The Notified Body GINGER CEBT, identification number nº 0074, performed the type tests and issued test report.

IDENTIFICATION:	CH040X
EDITION:	Fev 2022
VERSION:	6

INGLÈS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

N° DOP_CH040_2015_04

8. Declared performance:

EN 15651-1 : F EXT-INT CC:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL HARMONISED SPECIFICATION
Reaction to fire (EN 13501-1 + A1)	Class E	EN 15651-1 :2012
Water and air tightness as determined by:		
Loss of volume (EN ISO 10563)	≤ 10 %	EN 15651-1 :2012
Resistance to flow	≤ 3 mm	
Adhesion/cohesion determination of tensile properties at maintained extension after immersion in water (23°C) (EN ISO 10590)	NF	
Adhesion/cohesion determination of tensile properties at maintained extension at -30°C (EN ISO 8340 amended)	NF	
Durability (EN ISO 8340; EN ISO 9047; EN ISO 10590)	Compliant	

 Class: 25 HM
 Substrate: Mortar M1 without primer
 NF: No failure

EN 15651-4: PW EXT INT CC:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	TECHNICAL HARMONISED SPECIFICATION
Reaction to fire (EN 13501-1 + A1)	Class E	EN 15651-4 :2012
Water and air tightness as determined by:		
Loss of volume (EN ISO 10563)	≤ 10 %	EN 15651-4:2012
Tear resistance (EN ISO 8340 amended)	Compliant	
Adhesion/cohesion determination of tensile properties at maintained extension after immersion in water (28 days) (EN ISO 10590 amended)	NF	
Adhesion/cohesion determination of tensile properties at maintained extension after immersion in salt water (28 days) (EN ISO 10590 amended)	NF	
Adhesion/cohesion determination of tensile properties at maintained extension at -30°C (EN ISO 8340 amended)	NF	
Durability (EN ISO 8340; EN ISO 9047; EN ISO 10590)	Compliant	

 Class: 25 HM
 Substrate: Mortar M1 without primer
 NF: No failure

IDENTIFICATION:	CH040X
EDITION:	Fev 2022
VERSION:	6

INGLÊS | INGLÉS | ENGLISH

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Nº DOP_CH040_2015_04


9. Declaration:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Nuno Miranda
Diretor da Qualidade



Raquel Elias
Gestora de Produto

Aveiro (Portugal), 10.02.2022