

## SYNTHETIC DILUENT

# CHEMICLEAN SYNTHETIC DILUENT





#### PRODUCT DESCRIPTION

**CHEMICLEAN SYNTHETIC DILUENT** Diluent for diluting all synthetic products (paints, primers, undercoats, enamels and varnishes) with normal drying and also used for cleaning paint accessories, cleaning and degreasing tools and metal parts.

#### **CHARACTERISTICS**

- ✓ Professional Quality
- ✓ Normal drying synthetic based products dilution
- ✓ Excellent cleaning and degreasing agent for metal tools
- $\checkmark$  Cleans brushes, paintbrushes, rollers, spatulas and other painting accessories.

### **TECHNICAL SPECIFICATIONS**

Properties	Value		
Composition	Mixture of aromatic and aliphatic solvents		
Appearance	Clear		
Odor	Characteristic		
Color	10 Hazen		
Density at 20°C	Aprox. 0,85-0,90 g/cm <sup>3</sup>		
Solubility in water	Practically immiscible		
Humidity	≤1.0 %(m/m)		

Results tested in the laboratory.

#### **APPLICATIONS**

Diluent for diluting synthetic-based products (paints, undercoats, enamels and lacquers) except for quick-drying products and for cleaning and degreasing paint accessories, tools and metal parts.

#### **METHOD OF APPLICATION**

Use the product at room temperature.

It should be applied directly, pure or diluted, depending on the application and/or the surface to be cleaned

Make a previous test on a small area of the surface to be treated.



#### **SAFETY INFORMATION**

In general avoid contact with eyes and skin, wear gloves, goggles and appropriate clothing. Keep out of reach of children. Liquid and vapor easily flammable. Do not dispose of waste into the sewer. Do not ingest the product. For further information and advice on the safe handling, storage and disposal of chemicals, the user should refer to the most recent version of the Product Safety Data Sheet containing physical, ecological, toxicological and other safety-related

#### STORAGE CONDITIONS AND SHELF LIFE

Store the original package tightly closed, upright, in a cool, dry and well-ventilated environment, the storage area should not exceed extreme temperature conditions (5-30°C), away from heat sources, sunlight and moisture.

The product has a shelf life of 12 months when stored in its original container and in accordance with the storage conditions.

#### **PACKAGING**

SAP	Description	Volume L	<b>\Q</b>	EAN
CHC24030101	CHEMICLEAN SYNTHETIC DILUENT 1L	1	1	5604630147781
CHC24030105	CHEMICLEAN SYNTHETIC THINNER 5L	5	1	5604630147798

Note: This data sheet cancels and replaces others previously issued for the same product. The technical information provided, verbally or in writing, is based on our current knowledge and is given in good faith and supported by various laboratory tests. In view of the diversity of factors that can affect the product during use, as well as the varied application techniques, the user is responsible for confirming and performing his own tests and experiments, whether the product is suitable for the process and type of use in question. For these reasons, any application of the product is carried out under the sole responsibility of the user, and CHEMITOOL-LUSAVOUGA S.A. cannot be held liable for any loss or damage resulting directly or indirectly from the application. All features, specifications and product images are subject to change without notice.