

HYDROFUGANT ROOFS AND FACADES

PRODUCT DESCRIPTION

HYDROFUGANT ROOFS AND FACADES is a high-quality water repellent based on oligomeric siloxanes. Colourless waterproofing for porous materials, granite, marble, natural stones, tiles and other ceramics.

CHARACTERISTICS

- ✓ Professional Quality
- ✓ Colourless waterproofing of porous materials
- ✓ Excellent impregnation capacity and water repellent.
- ✓ Permeable to water vapour.
- ✓ Resistant to fungi and aging agents.

TECHNICAL SPECIFICATIONS

Properties	Value
Appearance	Liquid
Colour	Colorless
Odour	Characteristic
Density at 20°C	Aprox. 0,77
Drying Time (20°C; RH: 60%) Surface:	20 minutes
Repainting:	60 minutes

Laboratory test results.

CHEMICOAT HYDROFUGANT ROOFS AND FACADES



APPLICATIONS

Recommended for application on natural stone, cement, tiles, unglazed tiles, brick, plaster and other porous surfaces.

The durability of the product depends on the application, the surface and exposure to atmospheric agents, humidity, frost / thawing, among others.

METHOD OF APPLICATION

Dilution: Ready to apply.

Application Method: Brush, roller, sprayer or gun.

Performance: 8 to 10 m² / litre / coat. These values are indicative only, depending on the applicator and porosity of the surface.

PREPARATION

- The surfaces must be very clean and dry, degreased.
- The application must be carried out in dry weather. The surfaces must be very dry (risk of becoming whitish on contact with humidity)
- If the surface is contaminated with algae or moss, it should be rinsed with CHEMICLEAN -CLEANING ROOFS AND FACADE (SAP: CHC24040101)

METHOD OF APPLICATION

APPLICATION

- Carefully remove the packaging.
- It must be applied by spraying the surface to avoid the dispersion of the product, in smaller areas it can be applied with a brush.
- Apply two or three coats of HYDROFUGANT ROOFS AND FACADES, in order to impregnate the surface.
- On very porous surfaces, it may be necessary to increase the amount of product.

SAFETY INFORMATION

In general avoid contact with eyes and skin, wear gloves, goggles and appropriate clothing.

Keep out of reach of children. Use only in well-ventilated areas.


Do not empty into drains. Do not ingest the product. For further information and advice on the safe handling, storage and disposal of chemical products the user should refer to the most recent version of the Product Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

STORAGE CONDITIONS AND SHELF LIFE

Store the original package tightly closed, upright, in a cool, dry and well-ventilated environment, away from sources of heat and humidity.

The product is valid for 12 months if kept in its original packaging and in accordance with the storage conditions.

PACKAGING

SAP	Description	Volume L		EAN
CHC40020010050	CHEMICOAT HYDROFUGANT ROOFS AND FACADES	5	1	5604630147019

Note: This technical data sheet cancels and replaces others previously issued for the same product. The technical information provided, verbally or in writing, is based on our current knowledge and is provided in good faith and supported by various laboratory tests. In view of the diversity of factors which may affect the product during use, as well as the various application techniques, the user is responsible for confirming and carrying out his/her own tests and experiments, whether the product is suitable for the process and type of use in question. For these reasons, any application of the product is effected under the sole responsibility of the user, and CHEMITOOL- LUSAVOUGA S.A. cannot be held liable for any loss or damage resulting directly or indirectly from the application. All features, specifications and product images are subject to change without notice.