

CE  
CAT II




EN 388:2016  
  
4.X.4.3.D

## DOUBLE NITRILE COATED CUT RESISTANT GLOVE

Glove in spandex nylon, reinforced with HPPE and fiberglass with double nitrile coating. The full nitrile coating and the additional layer of sandy nitrile on the palm provide superior grip and protect the hand from oils, hydrocarbons, grease and abrasion. The seamless mesh reduces irritation and hand fatigue. It is a glove of great strength and performance recommended for the toughest and most demanding jobs.

- ✓ **Resistant to hydrocarbons**
- ✓ **Resistant to cut level D**
- ✓ **Resistant to abrasion level 4**
- ✓ **Oil resistant**
- ✓ **Greater dexterity**
- ✓ **Water resistant**
- ✓ **Seamless mesh**

### TECHNICAL SPECIFICATIONS

<b>Support</b>	HPPE, GLASS FIBER, NYLON SPANDEX		
<b>Coating</b>	NITRILE AND SANDY NITRILE FOAM		
<b>Color</b>	Blue		
<b>Size</b>	8/M – 9/L – 10/XL		
<b>Packaging</b>	1/12/120		
<b>General requirements and test methods</b>	EN ISO 21420:2020	Dexterity	<b>5</b>
<b>Mechanical Risks</b>	 EN 388:2016 4.X.4.3.D	Abrasion Resistance	0 1 2 3 <b>4</b>
		Blade Cut Resistance	0 1 2 3 4 5
		Tear Resistance	0 1 2 3 <b>4</b>
		Puncture Resistance	0 1 2 <b>3</b> 4
		Cut Resistance Method	A B C <b>D</b> E F
		Impact Protection	
<b>Uses</b>	Industry in general, automotive, metalwork, logistics, construction, mechanic workshops, handling materials with sharp, oily and wet surfaces.		

SAP	SIZE	EAN
CHS02020308	8/M	5604630113977
CHS02020309	9/L	5604630113984
CHS02020310	10/XL	5604630113991

## CARE, MAINTENANCE AND STORAGE

### PROTECTION LIMITS!

These gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire. These gloves are not waterproof, do not protect from fire and are not resistant to chemicals.

Contains natural rubber latex, which could cause allergic reaction, including anaphylactic shock.

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

### STORAGE

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

### PPE SUBJECT TO AGEING:

The design performance cannot be significantly affected by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

These gloves are a personal protective equipment belonging to category II.  
They comply with the requirements of the PPE Regulation 2016/425: safety, comfort, soundness, EN ISO 21420:2020 "Protective gloves - General requirements and test methods" and EN 388:2016+A1:2018 "Mechanical hazards".

PPE subject to an EU type-examination carried out by :  
C.T.C. (0075)  
4, rue Hermann Frenkel  
69367 Cedex LYON Cedex 07  
FRANÇA