

CE  
CAT II




EN 388:2016  
4.1.2.1.X

## NITRILE COATED POLYESTER GLOVE

General purpose glove made of Polyester with nitrile coating, seamless lining and elastic cuff to ensure a snug fit and prevent the ingress of debris and dirt. The ventilated back prevents hand perspiration and the nitrile coating gives maximum abrasion resistance. This glove is durable and resistant, suitable for a wide variety of jobs.

- ✓ **Breathable on the back**
- ✓ **Seamless mesh**
- ✓ **Oil resistant**
- ✓ **Abrasion resistant**
- ✓ **Flexible**

### TECHNICAL SPECIFICATIONS

<b>Support</b>	POLYESTER		
<b>Coating</b>	NITRILE		
<b>Color</b>	White and Grey		
<b>Size</b>	7/S - 8/M - 9/L - 10/XL - 11/XXL		
<b>Packaging</b>	1/12/120		
<b>General requirements and test methods</b>	EN ISO 21420:2020	Dexterity	5
<b>Mechanical Risks</b>	EN 388:2016  4.1.2.1.X	Abrasion Resistance	0 1 2 3 4
		Blade Cut Resistance	0 1 2 3 4 5
		Tear Resistance	0 1 2 3 4
		Puncture Resistance	0 1 2 3 4
		Cut Resistance Method	A B C D E F
		Impact Protection	
<b>Uses</b>	Industry in general, logistics, construction, automobile industry, aeronautics, transport.		

SAP	SIZE	EAN
CHS02110507	7/S	5604630114066
CHS02110508	8/M	5604630114073
CHS02110509	9/L	5604630114080
CHS02110510	10/XL	5604630114097
CHS02110511	11/XXL	5604630114103

## CARE, MAINTENANCE AND STORAGE

### PROTECTION LIMITS!

These gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire. These gloves are not waterproof, do not protect from fire and are not resistant to chemicals.

Contains natural rubber latex, which could cause allergic reaction, including anaphylactic shock.

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

### STORAGE

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

### PPE SUBJECT TO AGEING:

The design performance cannot be significantly affected by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

These gloves are a personal protective equipment belonging to category II.  
They comply with the requirements of the PPE Regulation 2016/425: safety, comfort, soundness, EN ISO 21420:2020 "Protective gloves - General requirements and test methods" and EN 388:2016+A1:2018 "Mechanical hazards".

PPE subject to an EU type-examination carried out by :  
C.T.C. (0075)  
4, rue Hermann Frenkel  
69367 Cedex LYON Cedex 07  
FRANÇA