

CE
 CAT II


LATEX COATED POLYESTER GLOVE

General purpose glove, manufactured using a seamless mesh lining, with a waterproof latex coated palm and elastic cuff that ensures a snug fit and prevents debris ingress. This open-back, breathable glove reduces perspiration, providing a high level of comfort, flexibility and softness. Latex provides a high level of elasticity, dexterity and excellent grip in wet and dry conditions.


- ✓ **Extra grip**
- ✓ **Seamless mesh**
- ✓ **Greater dexterity**
- ✓ **Breathable**
- ✓ **Flexible**

EN 388:2016



3.1.3.1.X

TECHNICAL SPECIFICATIONS

Support	POLYESTER		
Coating	LATEX		
Color	Red and Black		
Size	7/S - 8/M - 9/L - 10/XL - 11/XXL		
Packaging	1/12/120		
General requirements and test methods	EN ISO 21420:2020	Dexterity	5
Mechanical Risks	EN 388:2016  3.1.3.1.X	Abrasion Resistance	0 1 2 3 4
		Blade Cut Resistance	0 1 2 3 4 5
		Tear Resistance	0 1 2 3 4
		Puncture Resistance	0 1 2 3 4
		Cut Resistance Method	A B C D E F
		Impact Protection	
Uses	Industry in general, logistics, construction, automobile industry, aeronautics, transport, ceramic.		

SAP	SIZE	EAN
CHS02110807	7/S	5604630114165
CHS02110808	8/M	5604630114172
CHS02110809	9/L	5604630114189
CHS02110810	10/XL	5604630114196
CHS02110811	11/XXL	5604630114202

CARE, MAINTENANCE AND STORAGE

PROTECTION LIMITS!

These gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health. The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire. These gloves are not waterproof, do not protect from fire and are not resistant to chemicals.

Contains natural rubber latex, which could cause allergic reaction, including anaphylactic shock.

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

STORAGE

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

PPE SUBJECT TO AGEING:

The design performance cannot be significantly affected by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

These gloves are a personal protective equipment belonging to category II.
They comply with the requirements of the PPE Regulation 2016/425: safety, comfort, soundness, EN ISO 21420:2020 "Protective gloves - General requirements and test methods" and EN 388:2016+A1:2018 "Mechanical hazards".

PPE subject to an EU type-examination carried out by :
C.T.C. (0075)
4, rue Hermann Frenkel
69367 Cedex LYON Cedex 07
FRANÇA