

Review 1 01/09/2022

CHEMILUB

LUBRICANT GREASE GRAPHITE



LUBRICANT GREASE GRAPHITE

PRODUCT DESCRIPTION

CHEMILUB LUBRICANT GREASE GRAPHITE multifunctional grease with highly refined paraffinic base oils and lithium soap graphite.

PROPERTIES

- Excellent antiwear and extreme pressure properties.
- ✓ High protection against corrosion of metal parts.
- ✓ High resistance to aging, preventing compound degradation.
- Very good pumpability, including at low temperatures.
- ✓ Great mechanical resistance.

TECHNICAL SPECIFICATIONS

Properties	Standard	Value
Color	Visual	Black
Drop Point, °C (°F)	IP 396/ NFT 60- 267	215 °C
Penetration, 0.1 mm at 25 °C Not worked Worked x 60 strokes	ASTM D-217	310 305
Operating temperature		-30 °C a +215°C

Results were obtained under excellent environmental conditions.

APPLICATIONS

Recommended for general industry lubrication, lubrication in rolling mills or calenders by means of sliding pads

Intended for all types of bearings working under heavy loads, vibrations or in the presence of moisture (steelworks, mining and public works).

Field of application in a temperature range of -30 to 215° C.

METHOD OF APPLICATION

APPLICATION

. CHEMILUB LUBRICANT GREASE GRAPHITE can be applied by means of a lubricating pump, brush or spatula.



Review 1 01/09/2022

SAFETY INFORMATION

For more information and advice on the safe handling, storage and disposal of chemicals, the user should refer to the most recent version of the Product Safety Data Sheet containing physical, ecological, toxicological and other safety-related

STORAGE CONDITIONS

Store package upright in a cool, dry, well-ventilated environment away from sources of heat and humidity. Shelf life may exceed 5 years if stored properly.

PACKAGE AND COLOR

SAP	Descrição	₩	kg	\Q	EAN
CHC410102004	Lubricant Grease Graphite	Black	0,400	30	5604630146562
CHC41010205	Lubricant Grease Graphite	Black	5	1	5604630146579
CHC41010220	Lubricant Grease Graphite	Black	20	1	5604630146586
CHC41010250	Lubricant Grease Graphite	Black	50	1	5604630146593
CHC410102200	Lubricant Grease Graphite	Black	200	1	5604630146609

Note: This data sheet cancels and replaces others previously issued for the same product. The technical information provided, verbally or in writing, is based on our current knowledge and is given in good faith and supported by various laboratory tests. In view of the diversity of factors that can affect the product during use, as well as the varied application techniques, the user is responsible for confirming and performing his own tests and experiments, whether the product is suitable for the process and type of use in question. For these reasons, any application of the product is carried out under the sole responsibility of the user, and CHEMITOOL-LUSAVOUGA S.A. cannot be held liable for any loss or damage resulting directly or indirectly from the application. All features, specifications and product images are subject to change without notice.