

# BRAKE CLEANER

## CHEMISOL BRAKE CLEANER



### PRODUCT DESCRIPTION

Brake Cleaner CHEMISOL is a high quality product with excellent brake and metal dissolving properties. Removes oil, grease, brake fluid and brake dirt without leaving residue.

Isopropyl alcohol in the formula improves cleaning performance.

Evaporation is fast due to the low boiling point of the solvent.

### CHARACTERISTICS

- ✓ **Powerful cleaner and degreaser**
- ✓ **Leaves no residue**
- ✓ **Non-conductive**
- ✓ **Non corrosive to metals**

### TECHNICAL SPECIFICATIONS

Color	Transparent
Basis	aliphatic hydrocarbons
Odor	characteristic
Density relative to 20°C	0,675 – 0,688 g/ml
Kinematic viscosity at 20°C	0,5-1,4 mm <sup>2</sup> /s
Boiling temperature at atmospheric pressure	60 - 95°C
Vapor pressure at 20°C	6 kPa

These values may vary due to environmental factors such as temperature, humidity and type of substrate. The curing time is longer the lower the temperature and humidity and the thicker the product.

### APPLICATIONS

Recommended for drum brakes, disc brakes, brakes, calipers, brake shoes and brake calipers.

Cleaning and degreasing metals such as gear/engine parts.

Provides optimum friction between brake and clutch elements, improving braking effect.

### METHOD OF APPLICATION

#### APPLICATION

- Apply the product and let it act for a few seconds.
- The surface can be cleaned with a dry cloth. In case of heavy soiling, repeat the procedure.

## **RESTRICTIONS OF USE**

Due to the wide variety of possible substrates, a prior compatibility test is recommended.


## **SAFETY INFORMATION**

Follow the indications in the product safety data sheet.

## **STORAGE CONDITIONS**

Store in a cool, dry, well-ventilated environment between +5°C and +25°C, away from heat and moisture sources.

## **PACKAGING**

SAP	VOLUME		EAN
CHC020203	5 L	4	5604630050104
CHC020204	25 L	1	5604630050111
CHC020205	60 L	1	5604630050128

**Note:** This technical data sheet cancels and replaces others previously issued for the same product. The technical information provided, verbally or in writing, is based on our current knowledge and is provided in good faith and supported by various laboratory tests. In view of the diversity of factors which may affect the product during use, as well as the various application techniques, the user is responsible for confirming and carrying out his/her own tests and experiments, whether the product is suitable for the process and type of use in question. For these reasons, any application of the product is effected under the sole responsibility of the user, and CHEMITOOL- LUSAVOUGA S.A. cannot be held liable for any loss or damage resulting directly or indirectly from the application. All features, specifications and product images are subject to change without notice.