





## **MULTI-PURPOSE ALUMINIUM LADDER**

Aluminium multi-purpose ladder with platform. Ladder can be used in 3 different positions: extension ladder position, standing position and work platform (1400x290 mm). Comfortable non-slip rung (30x30 mm) and inner width of the ladder 285 mm. Multiusos hinges and slip-resistant cross-beam.

## **Features**

- ✓ Auto-lock safety system for the different positions
- Anti-slip stabilizer bases
- Aluminium side profile section 65 x 65 mm
- ✓ Step in aluminium section 30 x 30 mm with antiskid relief
- ✓ Stabilizing base with non-slip rubber feet
- ✓ Available in versions with 3 to 4 steps per flight
- ✓ Option of use with metallic platform

Certified to European standard EN131

## **TECHNICAL SPECIFICATIONS**

	الالا		<b>K</b> _	<b>↑</b>	max.	KG	1
REF	Steps	Maximum height of open ladder	Working height	Maximum working height	Useful working height of stepladder	Weight KG	Quantity per package
CHT200202010430	4 x 3	3,47 m	4,54 m	1,75 m	2,87 m	14,94 kg	1
CHT200202010440*	4 x 4	0 m	0 m	0 m	0 m	0 kg	1

<sup>\*</sup> Product not certified

SAP	Description	EAN	
CHT200202010430	Multi-purpose Aluminium Ladder 4 x 3 Steps	5604630130448	
CHT200202010440*	Multi-purpose Aluminium Ladder 4 x 4 Steps	5604630130431	

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control; therefore, we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusive to guarantee the quality of the products by our standards.\_REV\_11\_2022