



DIRTY WATER PUMP WITH STAINLESS STEEL BODY

Submersible Dirty Water Pump 550w and 1100w, ideal for drawing water from wells, tanks or swimming pools.

Maximum immersion depth up to 7m.

Maximum head up to 9.5m.

Maximum particle size 35mm.

Maximum flow rate up to 15000L/h.

Maximum fluid temperature 35°C.

Supply voltage 230 V 50 Hz.

Characteristics

- ✓ Cable: 10 meters
- ✓ Cable: H05RNF3G - 0.75mm²x10
- ✓ Heavy duty motor seal
- ✓ Stainless Steel Pump Body
- ✓ Float switch with adjustable height

TECHNICAL SPECIFICATIONS

SAP	CHG0040102005500	CHG0040102011000
Maximum head	7 m	9,5 m
Maximum flow rate	10500 L/h	15000 L/h
Tightness	IPX8	IPX8
Connections	1"; 1 1/4"; 1 1/2"	1"; 1 1/4"; 1 1/2"
Maximum immersion depth	7 m	7 m
Max. fluid temperature	35° C	35° C
Power supply cable	10 m	10 m
Body	Plastic / Stainless Steel	Plastic / Stainless Steel
Float switch	Yes	Yes
Power	550 W	1100 W
Maximum particle size	35 mm	35 mm
Supply voltage	230 V 50 Hz	230 V 50 Hz

SAP	Description	EAN
CHG0040102005500	Submersible Dirty Water Pump 550W	5604630139793
CHG0040102011000	Submersible Dirty Water Pump 1100W	5604630139809

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.