

CLEAN WATER PUMP WITH PLASTIC BODY



Submersible Clean Water Pump 250w and 400w, ideal for drawing water from wells, tanks or swimming pools.

Maximum immersion depth up to 7m.

Maximum head up to 7m.

Maximum particle size 5mm.

Maximum flow rate 7000L/h.

Maximum fluid temperature 35°C.

Supply voltage 230 V 50 Hz.

Characteristics

- ✓ Cable: 10 meters
- ✓ Cable: H05RNF3G - 0.75mm²x10
- ✓ Heavy duty motor seal
- ✓ Plastic Pump Body
- ✓ Float switch with adjustable height

TECHNICAL SPECIFICATIONS

Code	CHG0040101002500	CHG0040101004000
Maximum head	6 m	7 m
Maximum flow rate	5000 L/h	7000 L/h
Watertightness	IPX8	IPX8
Connections	1"; 1 1/4"; 1 1/2"	1"; 1 1/4"; 1 1/2"
Maximum immersion depth	5 m	7 m
Maximum fluid temperature	35° C	35° C
Power supply cable	10 m	10 m
Body	Plastic	Plastic
Float switch	Yes	Yes
Power	250 W	400 W
Maximum particle size	5 mm	5 mm
Supply voltage	230 V 50 Hz	230 V 50 Hz

SAP	Description	EAN
CHG0040101002500	Submersible Clean Water Pump 250 W	5604630139755
CHG0040101004000	Submersible Clean Water Pump 400 W	5604630139762

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.