

DIRTY WATER PUMP WITH PLASTIC BODY



Submersible Dirty Water Pump 400W, ideal for drawing water from wells, tanks or swimming pools.

Maximum immersion depth of 5m.

Maximum head of 5m.

Maximum particle size 35mm.

Maximum flow rate 7500L/h.

Maximum fluid temperature 35°C.

Supply voltage 230 V 50 Hz.

Characteristics

- ✓ Cable: 10 metres
- ✓ Cable: H05RNF3G - 0.75mm²x10
- ✓ Heavy duty motor seal
- ✓ Plastic Pump Body
- ✓ Float switch adjustable with height

TECHNICAL SPECIFICATIONS

Code	CHG0040102004000	
Maximum head	5 m	
Maximum flow rate	7500 L/h	
Watertightness	IPX8	
Connections	1"; 1 1/4"; 1 1/2"	
Maximum immersion depth	5 m	
Maximum fluid temperature	35° C	
Power supply cable	10 m	
Body	Plástico	
Float switch	Sim	
Power	400 W	
Maximum particle size	35 mm	
Supply voltage	230 V 50 Hz	
SAP	Description	EAN
CHG0040102004000	Dirty Water Submersible Pump 400 W	5604630139786

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.