

BOOSTER PUMP

Pressure boosting unit with a power of 800W and a 19L tank with anti-corrosion treatment that allows you to pump water from an alternative source to another location.

With a maximum flow rate of 3000 L/h it allows the transport of fluids up to 35°C and a maximum pressure of 3.0 bar, being an excellent and quick option to feed appliances such as washing machines, toilet tanks or the irrigation system for gardens and vegetable gardens, among others.

Characteristics

- ✓ Cable: 1.2 metres
- ✓ Cable: H05RNF3G - 0.75mm²x10
- ✓ Heavy duty motor seal
- ✓ Stainless steel pump body
- ✓ Painted steel tank



TECHNICAL SPECIFICATIONS

SAP	CHG0040201025000
Maximum head	40 m
Maximum flow rate	3000 L/h
Tightness	IPX8
Sound power level (LWA)	86 dB
Connections	1"
Maximum immersion depth	8 m
Maximum fluid temperature	35° C
Tank capacity	19 L
Tank material	Painted steel
Anti-corrosion treatment	Yes
Pressure	1,2~3,0 bar
Pump body	Cast iron
Power	800 W
Cable length	1,2 m
Supply voltage	230 V 50 Hz

SAP	Description	EAN
CHG0040201025000	800W stainless steel pressure boost with tank	5604630139823

Note: The technical information provided, verbally or in writing, is based on our current knowledge and should be regarded as non-binding collaboration. The use of the product is beyond our control, therefore we disclaim all liability for improper use of the product. The customer is responsible for confirming and evaluating (through testing) whether the product is suitable for the process and type of use in question. Our purpose is exclusively to guarantee the quality of the products in accordance with our standards.